Transitional Environmental Program
Transitional Environmental Program (TEP) E-100018841 relates to this permit and is in force until 31 December 2022. A copy of the TEP E-100018841 can be obtained from the administering authority. It is an offence to contravene a requirement of the TEP or a condition of the TEP approval.

Signed, **Delegate**
Date: **11 September 2020**

Permit
Environmental Protection Act 1994

Environmental authority EPPR00791913

This environmental authority is issued by the administering authority under Chapter 5 of the Environmental Protection Act 1994.

Environmental authority number: EPPR00791913

Environmental authority takes effect on 28 November 2018

Environmental authority holder(s)

Name(s)	Registered address
Isaac Regional Council	1 Batchelor Parade MORANBAH QLD 4744

Environmentally relevant activity and location details

Environmentally relevant activity/activities	Location(s)
Prescribed ERA, ERA 16 - Extraction and Screening, 2: Extracting, other than by dredging, in a year, the following quantity of material, (a) 5,000t to 100,000t	Lot 3/HLN29
Prescribed ERA, ERA 63 - Sewage Treatment, 1: Operating sewage treatment works, other than no-release works, with a total daily peak design capacity of, (b-i) more than 100 but not more than 1500EP if treated effluent is discharged from the works to an infiltration trench or through an irrigation scheme	Lot 98/SP159584
Prescribed ERA, ERA 63 - Sewage Treatment, 1: Operating sewage treatment works, other than no-release works, with a total daily peak design capacity of, (e) more than 10,000 but not more than 50,000EP	Lot 1/GV282
Prescribed ERA, ERA 63 - Sewage Treatment, 1: Operating sewage treatment works, other than no-release works, with a total daily peak design capacity of, (e) more than 10,000 but not more than 50,000EP	LOT 44/GV203
Prescribed ERA, ERA 60 - Waste disposal, 2: Operating a facility for disposing of, in a year, the following quantity of waste mentioned in subsection (1) (b), (b) more than 2000t but not more than 5000t	Lot 2/SP231842
Prescribed ERA, ERA 60 - Waste disposal, 2: Operating a facility for disposing of, in a year, the following quantity of waste mentioned in subsection (1) (b), (b) more than 2000t but not more than 5000t	Lot 98/SP159584

ABN 46 640 294 485
Queensland Government

Environmental authority

Environmentally relevant activity/activities	Location(s)
Prescribed ERA, ERA 60 - Waste disposal, 2: Operating a facility for disposing of, in a year, the following quantity of waste mentioned in subsection (1) (b), (b) more than 2000t but not more than 5000t	Lot 10/HLN205
Prescribed ERA, ERA 63 - Sewage Treatment, 1: Operating sewage treatment works, other than no-release works, with a total daily peak design capacity of, (d) more than 4000 but not more than 10,000EP	Lot 13/CNS116
Prescribed ERA, ERA 63 - Sewage Treatment, 1: Operating sewage treatment works, other than no-release works, with a total daily peak design capacity of, (c) more than 1500 but not more than 4000EP	LOT 1/CP884891
Prescribed ERA, ERA 63 - Sewage Treatment, 1: Operating sewage treatment works, other than no-release works, with a total daily peak design capacity of, (c) more than 1500 but not more than 4000EP	Lot 186/CLM370
Prescribed ERA, ERA 63 - Sewage Treatment, 1: Operating sewage treatment works, other than no-release works, with a total daily peak design capacity of, (c) more than 1500 but not more than 4000EP	Lot 5/CP884891
Prescribed ERA, ERA 63 - Sewage Treatment, 1: Operating sewage treatment works, other than no-release works, with a total daily peak design capacity of, (c) more than 1500 but not more than 4000EP	Lot 23/CNS211
Prescribed ERA, ERA 56 - Regulated Waste Storage, Receiving and storing regulated waste	Lot 2/SP231842
Prescribed ERA, ERA 56 - Regulated Waste Storage, Receiving and storing regulated waste	Lot 2/GV812139
Prescribed ERA, ERA 56 - Regulated Waste Storage, Receiving and storing regulated waste	LOT 228/CLM63
Prescribed ERA, ERA 63 - Sewage Treatment, 2: Operating a sewage pumping station mentioned in subsection (1)(b)	LOT 903/SP305818
Prescribed ERA, ERA 63 - Sewage Treatment, 2: Operating a sewage pumping station mentioned in subsection (1)(b)	Lot 2/GV812139
Prescribed ERA, ERA 63 - Sewage Treatment, 2: Operating a sewage pumping station mentioned in subsection (1)(b)	LOT 9/SP125734
Prescribed ERA, ERA 63 - Sewage Treatment, 2: Operating a sewage pumping station mentioned in subsection (1)(b)	LOT 36/GV267

ABN 46 640 294 485

Environmental authority

Environmentally relevant activity/activities	Location(s)
Prescribed ERA, ERA 63 - Sewage Treatment, 2: Operating a sewage pumping station mentioned in subsection (1)(b)	LOT 19/SP158749
Prescribed ERA, ERA 63 - Sewage Treatment, 2: Operating a sewage pumping station mentioned in subsection (1)(b)	LOT 100/SP228153
Prescribed ERA, ERA 63 - Sewage Treatment, 2: Operating a sewage pumping station mentioned in subsection (1)(b)	Adjacent to LOT 53/sp244521
Prescribed ERA, ERA 63 - Sewage Treatment, 2: Operating a sewage pumping station mentioned in subsection (1)(b)	LOT 900/SP256570
Prescribed ERA, ERA 63 - Sewage Treatment, 2: Operating a sewage pumping station mentioned in subsection (1)(b)	LOT 7/CP895140
Prescribed ERA, ERA 63 - Sewage Treatment, 2: Operating a sewage pumping station mentioned in subsection (1)(b)	LOT 27/SP101157
Prescribed ERA, ERA 63 - Sewage Treatment, 2: Operating a sewage pumping station mentioned in subsection (1)(b)	LOT 1/CP902901
Prescribed ERA, ERA 63 - Sewage Treatment, 2: Operating a sewage pumping station mentioned in subsection (1)(b)	LOT 600/SP184932
Prescribed ERA, ERA 63 - Sewage Treatment, 2: Operating a sewage pumping station mentioned in subsection (1)(b)	LOT 133/SP218567
Prescribed ERA, ERA 63 - Sewage Treatment, 2: Operating a sewage pumping station mentioned in subsection (1)(b)	Adjacent to LOT 1/SP125155
Prescribed ERA, ERA 63 - Sewage Treatment, 2: Operating a sewage pumping station mentioned in subsection (1)(b)	LOT 144/CLM498
Prescribed ERA, ERA 63 - Sewage Treatment, 2: Operating a sewage pumping station mentioned in subsection (1)(b)	LOT 143/CLM544
Prescribed ERA, ERA 63 - Sewage Treatment, 2: Operating a sewage pumping station mentioned in subsection (1)(b)	LOT 20/CNS322
Prescribed ERA, ERA 63 - Sewage Treatment, 2: Operating a sewage pumping station mentioned in subsection (1)(b)	LOT 4/SP193681

ABN 46 640 294 485

Environmentally relevant activity/activities	Location(s)
Prescribed ERA, ERA 63 - Sewage Treatment, 2: Operating a sewage pumping station mentioned in subsection (1)(b)	LOT 26/SP257930
Prescribed ERA, ERA 63 - Sewage Treatment, 2: Operating a sewage pumping station mentioned in subsection (1)(b)	LOT 901/SP235538
Prescribed ERA, ERA 63 - Sewage Treatment, 2: Operating a sewage pumping station mentioned in subsection (1)(b)	LOT 11/CNS115
Prescribed ERA, ERA 63 - Sewage Treatment, 2: Operating a sewage pumping station mentioned in subsection (1)(b)	LOT 17/HLN230
Prescribed ERA, ERA 63 - Sewage Treatment, 2: Operating a sewage pumping station mentioned in subsection (1)(b)	LOT 11/SP208044
Prescribed ERA, ERA 63 - Sewage Treatment, 2: Operating a sewage pumping station mentioned in subsection (1)(b)	LOT 4/SP253803
Prescribed ERA, ERA 63 - Sewage Treatment, 2: Operating a sewage pumping station mentioned in subsection (1)(b)	LOT 2/AP10097
Prescribed ERA, ERA 63 - Sewage Treatment, 2: Operating a sewage pumping station mentioned in subsection (1)(b)	LOT 25/CNS239
Prescribed ERA, ERA 63 - Sewage Treatment, 2: Operating a sewage pumping station mentioned in subsection (1)(b)	LOT 24/CNS240
Prescribed ERA, ERA 63 - Sewage Treatment, 2: Operating a sewage pumping station mentioned in subsection (1)(b)	LOT 26/CNS212
Prescribed ERA, ERA 63 - Sewage Treatment, 2: Operating a sewage pumping station mentioned in subsection (1)(b)	LOT 1/M112139
Prescribed ERA, ERA 63 - Sewage Treatment, 2: Operating a sewage pumping station mentioned in subsection (1)(b)	LOT 1/SP181424
Prescribed ERA, ERA 63 - Sewage Treatment, 2: Operating a sewage pumping station mentioned in subsection (1)(b)	Adjacent to LOT 159/N1101
Prescribed ERA, ERA 63 - Sewage Treatment, 2: Operating a sewage pumping station mentioned in subsection (1)(b)	LOT 35/SP178358

Environmentally relevant activity/activities	Location(s)
Prescribed ERA, ERA 63 - Sewage Treatment, 2: Operating a sewage pumping station mentioned in subsection (1)(b)	Adjacent to LOT 113/N1101
Prescribed ERA, ERA 63 - Sewage Treatment, 2: Operating a sewage pumping station mentioned in subsection (1)(b)	Adjacent to LOT 36/WHS349
Prescribed ERA, ERA 60 - Waste disposal, 2: Operating a facility for disposing of, in a year, the following quantity of waste mentioned in subsection (1)(b), (a) 50t to 2000t	LOT 11/SP301956
Prescribed ERA, ERA 60 - Waste disposal, 2: Operating a facility for disposing of, in a year, the following quantity of waste mentioned in subsection (1)(b), (a) 50t to 2000t	Lot 49/CNS281
Prescribed ERA, ERA 60 - Waste disposal, 2: Operating a facility for disposing of, in a year, the following quantity of waste mentioned in subsection (1)(b), (a) 50t to 2000t	Lot 1/SP201845
Prescribed ERA, ERA 60 - Waste disposal, 2: Operating a facility for disposing of, in a year, the following quantity of waste mentioned in subsection (1)(b), (a) 50t to 2000t	Lot 66/MUR40149
Prescribed ERA, ERA 60 - Waste disposal, 2: Operating a facility for disposing of, in a year, the following quantity of waste mentioned in subsection (1)(b), (a) 50t to 2000t	LOT 80/MC682
Prescribed ERA, ERA 60 - Waste disposal, 2: Operating a facility for disposing of, in a year, the following quantity of waste mentioned in subsection (1)(b), (a) 50t to 2000t	LOT 68/CP900902
Prescribed ERA, ERA 64 - Water treatment, 3: Treating 10ML or more raw water in a day	Lot 2/GV812139

Additional information for applicants

Environmentally relevant activities

The description of any environmentally relevant activity (ERA) for which an environmental authority (EA) is issued is a restatement of the ERA as defined by legislation at the time the EA is issued. Where there is any inconsistency between that description of an ERA and the conditions stated by an EA as to the scale, intensity or manner of carrying out an ERA, the conditions prevail to the extent of the inconsistency.

An EA authorises the carrying out of an ERA and does not authorise any environmental harm unless a condition stated by the EA specifically authorises environmental harm.

A person carrying out an ERA must also be a registered suitable operator under the Environmental Protection Act 1994 (EP Act).

Contaminated land

It is a requirement of the EP Act that an owner or occupier of contaminated land give written notice to the administering authority if they become aware of the following:

- the happening of an event involving a hazardous contaminant on the contaminated land (notice must be given within 24 hours); or
- a change in the condition of the contaminated land (notice must be given within 24 hours); or
- a notifiable activity (as defined in Schedule 3) having been carried out, or is being carried out, on the contaminated land (notice must be given within 20 business days);

that is causing, or is reasonably likely to cause, serious or material environmental harm.

For further information, including the form for giving written notice, refer to the Queensland Government website www.qld.gov.au, using the search term 'duty to notify'.

Take effect

Please note that, in accordance with section 200 of the EP Act, an EA has effect:

a) if the authority is for a prescribed ERA and it states that it takes effect on the day nominated by the holder of the authority in a written notice given to the administering authority-on the nominated day; or
b) if the authority states a day or an event for it to take effect-on the stated day or when the stated event happens; or
c) otherwise-on the day the authority is issued.

However, if the EA is authorising an activity that requires an additional authorisation (a relevant tenure for a resource activity, a development permit under the Planning Act 2016 or an SDA Approval under the State Development and Public Works Organisation Act 1971), this EA will not take effect until the additional authorisation has taken effect.

If this EA takes effect when the additional authorisation takes effect, you must provide the administering authority written notice within 5 business days of receiving notification of the related additional authorisation taking effect.

If you have incorrectly claimed that an additional authorisation is not required, carrying out the ERA without the additional authorisation is not legal and could result in your prosecution for providing false or misleading information or operating without a valid environmental authority.

Dorota Rosiak
Department of Environment and Science
Delegate of the administering authority
Environmental Protection Act 1994

Date issued: 28 November 2018

Enquiries:
Heritage, Utilities and Government Assessment
Department of Environment and Science
Phone: 1300 130 372
Email: palm@des.qld.gov.au

Obligations under the Environmental Protection Act 1994

In addition to the requirements found in the conditions of this environmental authority, the holder must also meet their obligations under the EP Act, and the regulations made under the EP Act. For example, the holder must comply with the following provisions of the Act:

- general environmental duty (section 319)
- duty to notify environmental harm (section 320-320G)
- offence of causing serious or material environmental harm (sections 437-439)
- offence of causing environmental nuisance (section 440)
- offence of depositing prescribed water contaminants in waters and related matters (section 440ZG)
- offence to place contaminant where environmental harm or nuisance may be caused (section 443)

Other permits required

This permit only provides an approval under the *Environmental Protection Act 1994*. In order to lawfully operate you may also require permits / approvals from your local government authority, other business units within the department and other State Government agencies prior to commencing any activity at the site. For example, this may include permits / approvals with your local Council (for planning approval), the Department of Transport and Main Roads (to access state controlled roads), the Department of Natural Resources and Mines (to clear vegetation), and the Department of Agriculture and Fisheries (to clear marine plants or to obtain a quarry material allocation).

Development Approval

This permit is not a development approval under the *Planning Act 2016*. The conditions of this environmental authority are separate, and in addition to, any conditions that may be on the development approval. If a copy of this environmental authority is attached to a development approval, it is for information only, and may not be current. Please contact the Department of Environment and Heritage Protection to ensure that you have the most current version of the environmental authority relating to this site.

Contents

Part	Environmentally relevant activities	Locations	
Part 1 – Standard conditions for sewage pump stations	ERA 63 Sewage treatment Threshold 2 operating a sewage pumping station mentioned in subsection (1)(b) >40KL/hour	SPMBH01	Adjacent to 53SP244521
		SPMBH02	9SP125734 - Forrest Drive
		SPMBH03	36GV267 - Jackson Avenue
		SPMBH04	900SP256570 - Utah Drive
		SPMBH05	7CP895140 - Colliery Street
		SPMBH06	2GV812139 - Goonyella Road
		SPMBH07	19SP158749 - Warne Court
		SPMBH08	27SP101157 - Grosvenor Drive
		SPMBH09	902SP278038 - Cunningham Way
		SPMBH10	1CP902901 - Leagues Club Access Road
		SPMBH11	600SP184932 - Nonette Street
		SPMBH12	133SP218567 - Langford Court
		SPMBH13	Adjacent to 1/SP125155
		SPMBH14	100SP228153 - Pumpstation Driveway (Thorpe St Estate).
		SPCLM01	144CLM498 - Cheeseborough Road
		SPCLM02	143CLM544 - Rubyvale Road
		SPDYS01	20CNS322 - Queen Elisabeth Drive - Major SPS located at CIVEO camp
		SPDYS02	4SP193681 - Edgerley Street
		SPDYS03	26SP257930 - Isaac Court
		SPDYS04	901SP235538 - Powell Street
		SPDYS05	11CNS115 - Fisher Street, Dysart
		SPGLN01	17HLN230 - Gilbert Avenue, Golf Club
		SPGLN02	11SP208044 - Gilbert Avenue
		SPGLN03	4SP253803 - Perry Drive
		SPGLN04	2AP10097 - Usher Terrace
		SPMMT01	25CNS239 - Centenary Drive North
		SPMMT02	24CNS240 - Centenary Drive South
		SPMMT03	26CNS212 - Centenary Drive North

		SPMMT04	1M112139 - Alfred Quinn Drive
		SPNBO01	1SP181424 - Cemetery Road
		SPNBO02	Adjacent to 159/N1101
		SPNBO03	35SP178358 - Airstrip Road
		SPNBO04	Adjacent to 113/N1101
		SPNBO05	Adjacent to 36/WHS349
Part 2 – General conditions for sewage/ extraction/ water treatment	16 Extractive and screening activities Threshold 2(a) extracting, other than by dredging, in a year, 5000-100,000t of material	Plum Tree Pit, Turwalla Rd Lot 3 Plan HLN29	
	ERA 64 Water treatment, Threshold 3 treating 10ML or more raw water in a day	145 Goonyella Rd Moranbah; Lot 2 on Plan GV321, and Lot 2 on Plan GV812139	
	ERA 63 Sewage Treatment, Threshold 1(b)(i) 100-1500EP IT or IR	Peak Downs Highway, Nebo; Lot 98 Plan SP159584	
	ERA 63 Sewage treatment, Threshold 1(c) operating sewage treatment works, other than no-release works, with a total daily peak design capacity of 1500-4000EP	Cheeseborough Rd Clermont; Reserve 165 Lot 186 Plan CLM370 106 Kurrajong Street Glenden; Lot 1 Plan CP884891, Lot 5 Plan CP884891 Fairway Drive Middlemount; Lot 23 Plan CNS211	
	ERA 63 Sewage treatment, Threshold 1(d) operating sewage treatment works, other than no-release works, with a total daily peak design capacity of 4000-10,000EP	Garnham Drive Dysart; Lot 13 Plan CNS116	
	ERA 63 Sewage treatment Threshold 1(e) operating sewage treatment works, other than no-release works, with a total daily peak design capacity of 10,000-50,000EP	Forrest Drive Moranbah; Lot 1 Plan GV282 and Lot 44 Plan GV203	
Part 3 – Specific conditions for water treatment	ERA 64 Water treatment, Threshold 3 treating 10ML or more raw water in a day	145 Goonyella Rd Moranbah; Lot 2 on Plan GV321, and Lot 2 on Plan GV812139	
Part 4 – Specific conditions for extraction	16 Extractive and screening activities Threshold 2(b) extracting, other than by dredging, in a year, 5000-100,000t of material	Plum Tree Pit, Turwalla Rd Lot 3 Plan HLN29	
Part 5 – General conditions for sewage treatment	ERA 63 Sewage Treatment, Threshold 1(b)(i) 100-1500EP IT or IR	Peak Downs Highway, Nebo; Lot 98 Plan SP159584	
	ERA 63 Sewage treatment, Threshold 1(c) operating sewage treatment works, other than no-release works, with a total daily peak design capacity of 1500-4000EP	Cheeseborough Rd Clermont; Reserve 165 Lot 186 Plan CLM370 106 Kurrajong Street Glenden; Lot 1 Plan CP884891, Lot 5 Plan CP884891 Fairway Drive Middlemount; Lot 23 Plan CNS211	

	ERA 63 Sewage treatment, Threshold 1(d) operating sewage treatment works, other than no-release works, with a total daily peak design capacity of 4000-10,000EP	Garnham Drive Dysart; Lot 13 Plan CNS116
	ERA 63 Sewage treatment Threshold 1(e) operating sewage treatment works, other than no-release works, with a total daily peak design capacity of 10,000-50,000EP	Forrest Drive Moranbah; Lot 1 Plan GV282 and Lot 44 Plan GV203
Part 6 – Site specific conditions for sewage treatment – Nebo	ERA 63 Sewage Treatment, Threshold 1(b)(i) 100-1500EP IT or IR	Peak Downs Highway, Nebo; Lot 98 Plan WHS327
Part 7 – Site specific conditions for sewage treatment – Moranbah	ERA 63 Sewage treatment Threshold 1(e) operating sewage treatment works, other than no-release works, with a total daily peak design capacity of 10,000-50,000EP	Forrest Drive Moranbah; Lot 1 Plan GV282 and Lot 44 Plan GV203
Definitions for Parts 1-7		
Part 8 – Waste, Former NM0140	ERA 60 Waste disposal, Threshold 2(b) operating a facility for disposing of, in a year, 2000-5000t of waste mentioned in subsection (1)(b)	Clermont Waste Management Facility: 38 Turama Rd, Clermont; Lot 2 on SP231842
	ERA 56 Regulated waste storage	Clermont Waste Management Facility: 38 Turama Rd, Clermont; Lot 2 on SP231842 Moranbah Works depot, Grosvenor Goonyella Rd Moranbah; Reserve 7 Lot 2 Plan GV321 Spoonbill Road, Clermont; Lot 228 CLM 63
Part 9 – Waste, Former NM0105	ERA 60 Waste disposal, Threshold 2(b) operating a facility for disposing of, in a year, 2000-5000t of waste mentioned in subsection (1)(b)	Nebo Waste Management Facility; 17914 Peak Downs Highway, Nebo; Lot 98 on SP159584 Glenden Waste Management Facility: 412 Ewan Drive, Glenden; Lot 10 Plan HLN205
Part 10 – Waste, Former NM0139	ERA 60 Waste disposal, Threshold 2(a) operating a facility for disposing of, in a year, 50-2000t of waste mentioned in subsection (1)(b)	Carmila Waste Management Facility: 153 Carmila West Road, Carmila; Lot 80 Plan MC682 Middlemount Waste Management Facility: 60 Nolan Drive, Middlemount; Lot 49 Plan CNS281 Dysart Waste Management Facility: 7145 Dysart-Clermont Road, Dysart; Lot 1 on SP201845 St Lawrence Waste Management Facility: 402 St Lawrence Connection Road, St Lawrence; Lot 66 Plan MUR40149 Greenhill Waste Management Facility: 1026 Greenhill Road, Ilbilbie; Lot 68 Plan MC683

Conditions of environmental authority

Part 1 – Standard conditions for sewage pump stations

Environmentally relevant activities	Locations	
ERA 63 Sewage treatment Threshold 2 operating a sewage pumping station mentioned in subsection (1)(b)	SPMBH01	Adjacent to 53SP244521
	SPMBH02	9SP125734 - Forrest Drive
	SPMBH03	36GV267 - Jackson Avenue
	SPMBH04	900SP256570 - Utah Drive
	SPMBH05	7CP895140 - Colliery Street
	SPMBH06	2GV812139 - Goonyella Road
	SPMBH07	19SP158749 - Warne Court
	SPMBH08	27SP101157 - Grosvenor Drive
	SPMBH09	902SP278038 - Cunningham Way
	SPMBH10	1CP902901 - Leagues Club Access Road
	SPMBH11	600SP184932 - Nonette Street
	SPMBH12	133SP218567 - Langford Court
	SPMBH13	Adjacent to 1/SP125155
	SPMBH14	100SP228153 - Pumpstation Driveway (Thorpe St Estate).
	SPCLM01	144CLM498 - Cheeseborough Road
	SPCLM02	143CLM544 - Rubyvale Road
	SPDYS01	20CNS322 - Queen Elisabeth Drive - Major SPS located at CIVEO camp
	SPDYS02	4SP193681 - Edgerley Street
	SPDYS03	26SP257930 - Isaac Court
	SPDYS04	901SP235538 - Powell Street
	SPDYS05	11CNS115 - Fisher Street, Dysart
	SPGLN01	17HLN230 - Gilbert Avenue, Golf Club
	SPGLN02	11SP208044 - Gilbert Avenue
	SPGLN03	4SP253803 - Perry Drive
	SPGLN04	2AP10097 - Usher Terrace
	SPMMT01	25CNS239 - Centenary Drive North
	SPMMT02	24CNS240 - Centenary Drive South
	SPMMT03	26CNS212 - Centenary Drive North

SPMMT04	1M112139 - Alfred Quinn Drive
SPNBO01	1SP181424 - Cemetery Road
SPNBO02	Adjacent to 159/N1101
SPNBO03	35SP178358 - Airstrip Road
SPNBO04	Adjacent to 113/N1101
SPNBO05	Adjacent to 36/WHS349

With the exception of any variations, the conditions of approval for the environmentally relevant activity conducted at the location described above must be conducted in accordance with the standard conditions contained within the attached document(s) entitled:

- *Code of environmental compliance for certain aspects of sewage treatment activities (ERA 63) (ESR/2015/1669) Version 1.*

Variations to the standard conditions include:

Condition 10 of the standard conditions is replaced by:	The operator must ensure that contaminants are not released to land or waters (including the bed and banks of any waters) as a result of the activity unless all reasonable and practicable measures have been taken to prevent the release.

Part 2 – General conditions for sewage/extraction/water treatment

Environmentally relevant activities	Locations
16 Extractive and screening activities Threshold 2(a) extracting, other than by dredging, in a year, 5000-100,000t of material	Plum Tree Pit, Turwalla Rd Lot 3 Plan HLN29
ERA 64 Water treatment, Threshold 3 treating 10ML or more raw water in a day	145 Goonyella Rd Moranbah; Lot 2 on Plan GV321, and Lot 2 on Plan GV812139
ERA 63 Sewage Treatment, Threshold 1(b)(i) 100-1500EP IT or IR	Peak Downs Highway, Nebo; Lot 98 Plan SP159584
ERA 63 Sewage treatment, Threshold 1(c) operating sewage treatment works, other than no-release works, with a total daily peak design capacity of 1500-4000EP	Cheeseborough Rd Clermont; Reserve 165 Lot 186 Plan CLM370 106 Kurrajong Street Glenden; Lot 1 Plan CP884891, Lot 5 Plan CP884891 Fairway Drive Middlemount; Lot 23 Plan CNS211
ERA 63 Sewage treatment, Threshold 1(d) operating sewage treatment works, other than no-release works, with a total daily peak design capacity of 4000-10,000EP	Garnham Drive Dysart; Lot 13 Plan CNS116
ERA 63 Sewage treatment Threshold 1(e) operating sewage treatment works, other than no-release works, with a total daily peak design capacity of 10,000-50,000EP	Forrest Drive Moranbah; Lot 1 Plan GV282 and Lot 44 Plan GV203

The environmentally relevant activities conducted at the locations as described above must be conducted in accordance with the following site specific conditions of approval:

Agency Interest: General	
Condition number	**Condition**
2-G1	All reasonable and practicable **measures** must be taken to prevent or minimise environmental harm caused by the **activities**.
2-G2	Any breach of a condition of this environmental authority must be reported to the **administering authority** as soon as practicable within 24 hours of becoming aware of the breach. **Records** must be kept including full details of the breach and any subsequent actions taken.
2-G3	The **activity** must be undertaken in accordance with written procedures that: 1. identify potential risks to the environment from the **activity** during routine operations, closure and an emergency 2. establish and maintain control **measures** that minimise the potential for environmental harm

	3. ensure plant, equipment and **measures** are maintained in a proper and effective condition 4. ensure plant, equipment and **measures** are operated in a proper and effective manner 5. ensure that staff are trained in and aware of their obligations under the *Environmental Protection Act 1994* 6. ensure that reviews of environmental performance are undertaken at least annually.
2-G4	All information and **records** required by the conditions of this environmental authority must be kept for a minimum of five years with the exception of environmental monitoring results which must be kept until surrender of this environmental authority. All information and **records** required by the conditions of this environmental authority must be provided to the **administering authority** upon request and in the format requested.
2-G5	An **appropriately qualified person(s)** must monitor, record and interpret all parameters that are required to be monitored by this environmental authority and in the manner specified by this environmental authority.
2-G6	All analyses required under this environmental authority must be carried out by a laboratory that has National Association of Testing Authorities (**NATA**) certification, or an equivalent certification, for such analyses. The only exception to this condition is for in situ monitoring of pH, Total Residual Chlorine, Total Suspended Solids, Ammonia, Dissolved Oxygen, and Electrical Conductivity where specified by the relevant monitoring condition.
2-G7	When required by the **administering authority**, monitoring must be undertaken in the manner prescribed by the **administering authority** to investigate a complaint of **environmental nuisance** arising from the **activity**. The monitoring results must be provided within 10 business days to the **administering authority** upon its request.
2-G8	An annual monitoring report must be prepared and submitted to the **administering authority** by 30 November each year, for the preceding financial year.
2-G9	All batteries, **liquid** chemicals, fuels, and other **liquid** substances with potential to cause environmental harm must be stored within a secondary containment system that is impervious to the materials stored within it, and must be managed to prevent the release of contaminants to **waters** or land.
2-G10	Excepting combustion of landfill gas, waste must not be burnt.
2-G11	All waste generated in carrying out the **activity** must be lawfully disposed of, reused, recycled or removed to a facility that can lawfully accept the waste.
2-G12	**You** must record the following details for all environmental complaints received: 1. date and time complaint was received 2. name and contact details of the complainant when provided and authorised by the complainant 3. nature of the complaint 4. investigations undertaken 5. conclusions formed 6. actions taken.

Agency Interest: Acoustic	
Condition number	**Condition**
2-N1	Other than as permitted within this environmental authority, noise generated by the **activity** must not cause **environmental nuisance** to any **sensitive place** or **commercial place.**
Agency Interest: Air	
Condition number	**Condition**
2-A1	Other than as permitted within this **environmental authority**, odours or airborne contaminants must not cause **environmental nuisance** to any **sensitive place** or **commercial place**.
Agency Interest: Land	
Condition number	**Condition**
2-L1	Other than as permitted within this environmental authority, contaminants must not be released to **land.**
Agency Interest: Water	
Condition number	**Condition**
2-WT1	Other than as permitted within this environmental authority, contaminants must not be released to any **waters**.
2-WT2	Permitted releases to **waters** must not produce any slick or other visible evidence of oil or grease, nor contain visible floating oil, grease, scum, litter or other visually objectionable matter.

Part 3 – Specific conditions for water treatment

Environmentally relevant activities	Locations
ERA 64 Water treatment, Threshold 3 treating 10ML or more raw water in a day	145 Goonyella Rd Moranbah; Lot 2 on Plan GV321, and Lot 2 on Plan GV812139

The environmentally relevant activities conducted at the locations as described above must be conducted in accordance with the following site specific conditions of approval:

Agency Interest: Land	
Condition number	**Condition**
3-L1	The environmentally relevant **activity** must be carried out by such practicable means necessary to prevent or minimise the release or likelihood of release of contaminants to land.
Agency Interest: Water	
Condition number	**Condition**
3-WT1	The environmentally relevant **activity** must be carried out by such practicable means necessary to prevent or minimise the release or likelihood of release of contaminants to water.
3-WT2	All sludge drying beds must be bunded.

Part 4 – Specific conditions for extraction

Environmentally relevant activities	Locations
16 Extractive and screening activities Threshold 2(a) extracting, other than by dredging, in a year, 5000-100,000t of material	Plum Tree Pit, Turwalla Rd Lot 3 Plan HLN29

The environmentally relevant activities conducted at the locations as described above must be conducted in accordance with the following site specific conditions of approval:

Agency Interest: Land	
Condition number	**Condition**
4-L1	**Land** that has been disturbed for **activities** conducted under this environmental authority must be rehabilitated in a manner such that: 1. suitable native species of vegetation for the location are established and sustained for earthen surfaces; 2. potential for erosion is minimised; 3. the quality of water released from the site, including seepage, does not cause environmental harm; 4. potential for **environmental nuisance** caused by dust is minimised; 5. the water quality of any residual water body does not have potential to cause environmental harm; 6. the final landform is stable and protects public safety.
4-L2	Rehabilitation of **disturbed areas** required under condition 4-L1 must take place progressively as works are staged and new extraction areas are commenced.
Agency Interest: Acoustic	
Condition number	**Condition**
4-N1	**Blasting** or the generation of **substantial low frequency noise** is not permitted.
Agency Interest: Water	
Condition number	**Condition**
4-WT1	Stormwater runoff from **disturbed areas** of the site, generated by (up to and including) a **24 hour storm event with an average recurrence interval of 1 in 5 years** must be retained on site or managed to remove contaminants prior to release.

Part 5 – General conditions for sewage treatment

Environmentally relevant activities	Locations
ERA 63 Sewage Treatment, Threshold 1(b)(i) 100-1500EP IT or IR	Peak Downs Highway, Nebo; Lot 98 Plan SP159584
ERA 63 Sewage treatment, Threshold 1(c) operating sewage treatment works, other than no-release works, with a total daily peak design capacity of 1500-4000EP	Cheeseborough Rd Clermont; Reserve 165 Lot 186 Plan CLM370 106 Kurrajong Street Glenden; Lot 1 Plan CP884891, Lot 5 Plan CP884891 Fairway Drive Middlemount; Lot 23 Plan CNS211
ERA 63 Sewage treatment, Threshold 1(d) operating sewage treatment works, other than no-release works, with a total daily peak design capacity of 4000-10,000EP	Garnham Drive Dysart; Lot 13 Plan CNS116
ERA 63 Sewage treatment Threshold 1(e) operating sewage treatment works, other than no-release works, with a total daily peak design capacity of 10,000-50,000EP	Forrest Drive Moranbah; Lot 1 Plan GV282 and Lot 44 Plan GV203

The environmentally relevant activities conducted at the locations as described above must be conducted in accordance with the following site specific conditions of approval:

Agency Interest: General	
Condition number	**Condition**
5-G1	**Activities** conducted under this environmental authority must not be conducted contrary to any of the following limitations: a) The wet weather storage at the Glenden Sewage Treatment Plant located at Lot 5 Plan CP884891 must be designed to contain 28 **days** expected maximum effluent flow.
5-G2	A **receiving environment monitoring program** must be designed and implemented by an **appropriately qualified person(s)** to monitor the effects of the **activity** on land.
5-G3	In regards to land, the **receiving environment monitoring program** required by condition 5-G2 must include at least the following: 1. An annual soil survey must be undertaken to ensure that the capacity of the land to assimilate nitrogen, phosphorus, salts and organic matter has not been exceeded. This must include annual soil monitoring of the parameters specified *in Table 5.1 – Soil Quality Characteristics*. 2. Soil sampling must be undertaken at representative locations within the land application area by an **appropriately qualified person**. 3. Observations must be recorded at the time of sampling with respect to the following considerations: a. Soil moisture content

<table>
<tr><td></td><td>
b. Soil texture
c. Plant cover and general health
d. Indicators of surface runoff occurring within the disposal area,
e. Evidence of surface ponding of water
f. Evidence of declining soil quality through subsidence, salinity or soil loss
g. General matters relating to the health and operation of the irrigation area

Table 5.1 – Soil Monitoring Quality Characteristics
<table>
<tr><th>Quality characteristics</th><th>Units</th></tr>
<tr><td>pH</td><td>pH units</td></tr>
<tr><td>Electrical Conductivity</td><td>µs/cm</td></tr>
<tr><td>Available Phosphorus</td><td>mg/kg</td></tr>
<tr><td>Available Potassium</td><td>mg/kg</td></tr>
<tr><td>Total Nitrogen</td><td>mg/kg</td></tr>
<tr><td>Total cations (inc. Na, Ca, Mg, K)</td><td>mg/kg</td></tr>
<tr><td>Cation exchange</td><td>capacity meq/100g</td></tr>
<tr><td>Exchangeable sodium</td><td>percentage meq/100g</td></tr>
<tr><td>Chloride</td><td>mg/kg</td></tr>
<tr><td>Heavy metals (As, Cd, Cr, Cu, Pb, Ni, Zn)</td><td>mg/kg</td></tr>
<tr><td>Organic carbon</td><td>%</td></tr>
</table>
</td></tr>
<tr><td>5-G8</td><td>
In regards to the receiving environment monitoring program required by condition 5-G2 for monitoring the effects of the activity on land, a report must be submitted annually to the administering authority, consisting of an analysis and interpretation of monitoring results by an appropriately qualified person, containing at least the following:
1. The effluent irrigation locations for all irrigation that was undertaken during the investigation period, identified on a scaled map; and
2. The monitoring locations for all monitoring undertaken during the investigation period, identified on a scaled map, with a justification for the selection of the monitoring locations and the number of monitoring locations chosen; and
3. Reference to the monitoring and quality assurance/quality control procedures followed for all monitoring undertaken; and
4. A determination of whether irrigation of effluent to land has impacted on any environmental values of the receiving environment, and the extent to which they have impacted on the environmental values during the investigation period;
5. A comparison of the quality of the current receiving environment to its historical quality based on past REMP results or other available monitoring studies, with regard to whether the releases from the activity are adversely impacting environmental values in the long term; and
6. Recommendations for:
a. whether further investigation is required to determine the extent of impacts on environmental values from the releases; and
b. whether any changes to REMP for future investigations are required; and
c. whether any changes to how the irrigation is carried out to prevent or minimise impacts on environmental values from the releases are required, and what those changes should be.
</td></tr>
</table>

<table>
<tr><th colspan="2">Agency Interest: Water</th></tr>
<tr><th>Condition number</th><th>Condition</th></tr>
<tr><td>5-WT1</td><td>All sludge drying beds must be bunded.</td></tr>
<tr><th colspan="2">Agency Interest: Land</th></tr>
<tr><th>Condition number</th><th>Condition</th></tr>
<tr><td>5-L1</td><td>The only contaminants to be released to land are treated sewage effluent in accordance with Table 5.2 - Treated effluent release limits to irrigation area and the associated requirements.

Table 5.2 - Treated effluent release limits to irrigation area
<table>
<tr><th>Water Quality Parameters</th><th>Minimum</th><th>Yearly maximum mean</th><th>Maximum</th><th>Frequency of Monitoring</th></tr>
<tr><td>Residual Chlorine (mg/L)</td><td>0.5</td><td>-</td><td>3.0</td><td>Daily in-situ, monthly by NATA accredited laboratory</td></tr>
<tr><td>pH (pH units)</td><td>6.0</td><td>-</td><td>8.5</td><td>Daily in-situ, monthly by NATA accredited laboratory</td></tr>
<tr><td>E.Coli (CFU/100mL)</td><td>-</td><td>-</td><td>10</td><td>Weekly</td></tr>
<tr><td>Total Suspended Solids (mg/L)</td><td>-</td><td>-</td><td>30</td><td>Monthly</td></tr>
<tr><td>Total Nitrogen (mg/L)</td><td>-</td><td>-</td><td>30</td><td>Monthly</td></tr>
<tr><td>Total Phosphorous (mg/L)</td><td>-</td><td>-</td><td>15</td><td>Monthly</td></tr>
<tr><td>Electrical conductivity (µS/cm)</td><td>-</td><td>1600</td><td>-</td><td>Monthly</td></tr>
<tr><td>BOD5 (mg/L)</td><td>-</td><td></td><td>20</td><td>Quarterly</td></tr>
</table>
Associated requirements
1. The daily quantity of effluent released must be determined or estimated by an appropriate method.
2. The defined contaminant release areas are landscaped areas of the approved place and public open space maintained by Isaac Regional Council.
3. Monitoring must be in accordance with the administering authority's Water Quality Sampling Manual and all monitoring devices must be effectively calibrated and maintained.
4. Monitoring must be undertaken when treated sewage effluent is being irrigated, unless irrigation has ceased for longer than the relevant parameters specified minimum frequency (e.g. if TSS was only required to be monitored once a week, then a TSS sample would not be required after the first week following cessation of the release).</td></tr>
<tr><td>5-L2</td><td>You must develop and implement an Irrigation Management Plan which details how the effluent irrigation process will be effectively and appropriately managed so as to ensure that the release of effluent to land is carried out in an environmentally sustainable manner.</td></tr>
<tr><td>5-L3</td><td>Irrigation of treated sewage effluent must be undertaken in accordance with the Irrigation Management Plan, and:
1. Must not exceed 5mm/day at any location;</td></tr>
</table>

	2. The average daily volume of treated effluent to be irrigated must not exceed 2.8mm/day calculated over an annual basis; 3. The following irrigation horizontal separation distances must be maintained: a. 30m must be left between the effluent disposal area and any permanent/intermittent watercourses on the site; b. 2m must be left between the effluent disposal area and the property **boundary**; and c. 5m must be left between the effluent disposal area and a sensitive receptor.
5-L4	Treated effluent released to land must be done in accordance with documentation that ensures: a) drainage to **groundwater** and subsurface flows of contaminants to surface **waters** are prevented b) surface pondage and run-off of effluent is prevented c) degradation of soil structure is minimised d) soil sodicity and the build-up of nutrients and heavy metals in the soil and subsoil are minimised e) spray drift or overspray does not carry beyond effluent disposal areas f) effluent disposal areas are maintained with an appropriate crop in a viable state for transpiration and nutrient uptake g) sufficient buffer zones are maintained between irrigation sites and sensitive environmental receptors h) release of treated effluent to land will not result in adverse public health issues.
5-L5	When weather conditions or soil conditions preclude the release of treated sewage effluent to land, effluent must not be irrigated to land.
5-L6	Treated sewage effluent may be removed from the site and used for an alternate purpose, with the written consent of any third party involved.

Part 6 – Site specific conditions for sewage treatment – Nebo

Environmentally relevant activities	Locations
ERA 63 Sewage Treatment, Threshold 1(b)(i) 100-1500EP IT or IR	Peak Downs Highway, Nebo; Lot 98 Plan WHS327

The environmentally relevant activities conducted at the locations as described above must be conducted in accordance with the following site specific conditions of approval:

Agency Interest: General	
Condition number	**Condition**
6-G1	**Activities** conducted under this environmental authority must not be conducted contrary to any of the following limitations: a) Inflows must not exceed the peak design capacity of 373,000 L/day on any **day**.
Agency Interest: Acoustic	
Condition number	**Condition**
6-N1	Noise from the **activity** must not include **substantial low frequency noise** components and must not exceed the levels identified in *Table 6.1 – Noise limits* and the associated requirements at any nuisance **sensitive place** or **commercial place**.
6-N2	When requested by the **administering authority**, noise monitoring must be undertaken to investigate any complaint of noise nuisance, and the results notified within 14 **days** to the **administering authority**. Monitoring must include: a) $L_{A\ 10,\ adj,\ 10\ mins}$

Table 6.1 – Noise limits

Noise level dB(A) measured as	Monday to Saturday			Sundays and public holidays		
	7am-6pm	6pm-10pm	10pm-7am	9am-6pm	6pm-10pm	10pm-9am
	Noise measured at a Noise sensitive place					
$L_{A10,\ adj,\ 10\ mins}$	55	50	40	55	50	40
$L_{A1,\ adj,\ 10\ mins}$	60	55	45	60	55	45
	Noise measured at a Commercial place					
$L_{A10,\ adj,\ 10\ mins}$	60	55	45	60	55	45
$L_{A1,\ adj,\ 10\ mins}$	65	60	50	65	60	50

Associated requirements

1. All monitoring devices must be effectively calibrated and maintained.
2. Monitoring must be taken when emissions are expected to be representative of actual operating conditions for the sample frequency period.
3. Noise monitoring must be in accordance with the most recent version of the **administering authority's** Noise Measurement Manual.

	b) $L_{A\ 1,\ adj,\ 10\ mins}$ c) the level and frequency of occurrence of impulsive or tonal noise; d) atmospheric conditions including wind speed and direction; e) effects due to extraneous factors such as traffic noise; and f) location, date and time of recording.
Agency Interest: Water	
Condition number	**Condition**
6-WT1	All ponds used for the storage or treatment of contaminants, sewage or wastes at or on the authorised place, must be constructed, installed and maintained: a) so as to minimise the likelihood of any release of effluent through the bed or banks of the pond to any **waters** (including **groundwater**); b) so that a freeboard of not less than 0.5 metres is maintained at all times, except in emergencies; and c) so as to ensure the stability of the ponds' construction.
6-WT2	The effluent lagoon floor must achieve a permeability of 1×10^{-8} m/s.
6-WT3	Diversion drains installed to exclude stormwater runoff from structures used for the storage or treatment of contaminants or wastes must be capable of diverting stormwater from a **24 hour storm event with an average recurrence interval of 1 in 10 years**.

Part 7 – Site specific conditions for sewage treatment – Moranbah

Environmentally relevant activities	Locations
ERA 63 Sewage treatment Threshold 1(e) operating sewage treatment works, other than no-release works, with a total daily peak design capacity of 10,000-50,000EP	Forrest Drive Moranbah; Lot 1 Plan GV282 and Lot 44 Plan GV203

The environmentally relevant activities conducted at the locations as described above must be conducted in accordance with the following site specific conditions of approval:

Agency Interest: General	
Condition number	**Condition**
7-G1	**Activities** conducted under this environmental authority must not be conducted contrary to any of the following limitations: 1. Inflows must not exceed the peak design capacity of 3.6 ML/**day** for the main sewage treatment plant on the site. 2. Inflows must not exceed the peak design capacity of 0.9 ML/**day** for the support sewage treatment plant on the site. 3. Daily inflow must be determined or estimated by an appropriate method with an accuracy of +/- 5%.
7-G2	A **receiving environment monitoring program** must be designed and implemented by an **appropriately qualified person(s)** to monitor the effects of the **activity** on surface **waters**, and **groundwater**.
7-G3	In regards to surface **waters**, the **receiving environment monitoring program** required by condition 7-G2, must include at least the following: 1. A description of potentially affected receiving **waters** including key communities and background water and sediment quality characteristics based on accurate and reliable monitoring data that takes into consideration any temporal variation (e.g. seasonality); and 2. A description of applicable **environmental values** of the receiving environment, and sediment and water quality objectives to be achieved, and 3. Reference to any relevant reports prepared by other governmental or professional research organisations that relate to the receiving environment within which the **receiving environment monitoring program** is proposed; and 4. Water and sediment quality targets within the receiving environment to be achieved; and 5. Clarification of contaminant concentrations or levels indicating adverse environmental impacts during the monitoring program.
7-G4	In regards to the **receiving environment monitoring program** required by condition 7-G2 for monitoring the effects of the **activity** on surface **waters**, a report must be submitted annually to the **administering authority**, consisting of an analysis and interpretation of monitoring results by an **appropriately qualified person**, containing at least the following:

	1. The volume of effluent released to creek during the investigation period for the report, and quality of the releases; and 2. The monitoring locations for all monitoring undertaken during the investigation period, identified on a scaled map, with a justification for the selection of the monitoring locations and the number of monitoring locations chosen; and 3. Justification for the selected frequency of monitoring; and 4. Justification for the selected quality characteristics monitored; and 5. Reference to the monitoring and quality assurance/quality control procedures followed for all monitoring undertaken; and 6. A determination of whether releases have impacted on the hydrological processes of the receiving environment; and 7. A determination of whether releases have impacted on any **environmental values** of the receiving environment, and the extent to which they have impacted on the **environmental values** during the investigation period; and 8. A comparison of the quality of the current receiving environment to its historical quality based on past REMP results or other available monitoring studies, with regard to whether the releases from the **activity** are adversely impacting **environmental values** in the long term; and 9. Recommendations for: a. whether further investigation is required to determine the extent of impacts on **environmental values** from the releases; and b. whether any changes to REMP for future investigations are required; and c. whether any changes to how the **activity** is operated to prevent or minimise impacts on **environmental values** from the releases are required, and what those changes should be.
7-G5	In regards to **groundwater**, the **receiving environment monitoring program** required by condition 7-G2 must include at least the following: 1. Development of a suitable **groundwater** monitoring network, to monitor the quality of **groundwater** potentially impacted by any direct or indirect release of contaminants associated with the **activity**. This network must: a. be installed and maintained by an **appropriately qualified person**; and b. be constructed in accordance with the National Uniform Drillers Licensing Committee manual titled *Minimum Construction Requirements for Water Bores in Australia, Edition 3, Revised February 2012,* or more recent editions or supplements to that document as such become available; and 2. The **groundwater** bores in the **groundwater** monitoring network must be hydrologically located to detect potential **groundwater** impacts from irrigating treated effluent to land, the sewage treatment plant and include a reference (non-impacted) site; and 3. All determinations of the quality of contaminants released to **waters** must be made in accordance with, but are not limited to, methods prescribed in: AS/NZS 5667:11:1998 —Water Quality —Sampling —Guidance on sampling of **groundwaters**, or more recent editions or supplements to that document as such become available; and/or **administering authority's** Monitoring and Sampling Manual, or more recent editions or supplements to that document as such become available; and

4. **Groundwater** samples taken from the bores must be analysed for, but are not limited to, the water quality parameters required in *Table 7.1- Groundwater Quality Characteristics*; and
5. Standing water levels and total well depths in metres must be measured and recorded during each sampling event. Such measurements must be undertaken prior to any disturbance by sampling activities and must be reported as the depth in metres from the top edge of the highest point of the casing collar to the water surface within the bore; and
6. **Groundwater** samples taken from the bores must be representative of the aquifer(s); and
7. **Groundwater** samples must be taken from each of the bores before commencement of the environmentally relevant **activity** and during each sampling event.

Table 7.1 – Groundwater Monitoring Quality Characteristics

Water Quality Parameters	Units	Monitoring Frequency
pH	pH units	Every 6 months from commencement of the issue of the permit. After 4 monitoring events on commencement of irrigation, the **administering authority** based on the findings of the **Groundwater** Monitoring Analysis Report may approve monitoring to be conducted annually.
Electrical Conductivity	µS/cm	
Total Nitrogen (as N)	mg/L	
Ammonia (as N)	mg/L	
Nitrite (as N)	mg/L	
Nitrate (as N)	mg/L	
Total Phosphorus (as P)	mg/L	
E. Coli	CFU/100mL	
BOD5	mg/L	

7-G6

In regards to the **receiving environment monitoring program** required by condition 7-G2 for monitoring the effects of the **activity** on **groundwater**, a report must be submitted annually to the **administering authority**, consisting of an analysis and interpretation of monitoring results by an **appropriately qualified person**, containing at least the following:

1. The location of the **groundwater** bores; and
2. The nature (confined, unconfined etc.) of the aquifer; and
3. The water quality of each aquifer; and
4. Defined **groundwater** contours; and
5. An indication of direction of flow; and
6. An assessment of the nature and extent of any environmental harm caused by the **activity** on **groundwater**.

Agency Interest: Acoustic

Condition number	Condition
7-N1	Noise from the **activity** must not include **substantial low frequency noise** components and must not exceed the levels identified in *Table 7.2 – Noise limits*

<table>
<tr><td></td><td>and the associated requirements at any nuisance sensitive place or commercial place.

Table 7.2 – Noise limits
<table>
<tr><td rowspan="2">Noise level dB(A)</td><td colspan="3">Monday to Sunday (including public holidays)</td></tr>
<tr><td>7am – 6pm</td><td>6pm – 10pm</td><td>10pm – 7am</td></tr>
<tr><td></td><td colspan="3">Noise measured at a sensitive place or commercial place</td></tr>
<tr><td>$L_{A10, adj, 10 mins}$</td><td>Background + 5</td><td>Background + 5</td><td>Background + 3</td></tr>
<tr><td>$L_{A1, adj, 10 mins}$</td><td>Background + 10</td><td>Background + 10</td><td>Background + 5</td></tr>
</table>
Associated Monitoring Requirements
1. Limits are applied at the boundary of the sensitive or commercial place.
2. The location, date and time of monitoring must be recorded.
3. All monitoring devices must be correctly calibrated and maintained.
4. Any monitoring must be in accordance with the most recent version of the administering authority's Noise Measurement Manual.
5. Any monitoring of noise emissions from the activity must be undertaken when the activity is in operation.
6. All monitoring must be performed by an appropriately qualified person(s).</td></tr>
<tr><td>7-N2</td><td>When required by the administering authority, noise monitoring must be undertaken, in accordance with the associated monitoring requirements of Table 7.2 – Noise limits in condition 7-N1, and the results notified within 14 days to the administering authority. Monitoring must include:
a) Background noise level $L_{A10, adj, 10 mins}$
b) $L_{A1, adj, 10 mins}$
c) $L_{Amax, adj, T}$
d) the level and frequency of occurrence of any impulsive or tonal noise
e) atmospheric conditions including wind speed and direction
f) effects due to extraneous factors such as traffic noise
g) location, date and time of recording.</td></tr>
<tr><td colspan="2">Agency Interest: Air</td></tr>
<tr><td>Condition number</td><td>Condition</td></tr>
<tr><td>7-A1</td><td>Dust and particulate matter emissions must not exceed the following concentrations at any sensitive place or commercial place:
a) dust deposition of 120 milligrams per square metre per day, when monitored in accordance with Australian Standard AS 3580.10.1 (or more recent editions), or
b) a concentration of particulate matter with an aerodynamic diameter of less than 10 micrometre (µm) (PM_{10}) suspended in the atmosphere of 50 micrograms per cubic metre over a 24 hour averaging time, when monitored in accordance with Australian Standard AS 3580.9.6 (or more recent editions) or any other method approved by the administering authority.</td></tr>
</table>

Agency Interest: Water

Condition number	Condition
7-WT1	The only contaminants to be released to surface **waters** are from the effluent storage **dams** (Mo-ESP1 and Mo-ESP2) to **waters** described as Grosvenor Creek, at release point W1 (located at Longitude: 148.045, Latitude: -22.0136) in accordance with *Table 7.3 - Surface water release limits* and the associated requirements.

Table 7.3 – Surface water release limits

Release point	Quality characteristic	Units	Minimum	Mean	Median	Maximum	Monitoring Frequency
W1 (located at Longitude: 148.045, Latitude: -22.0136)	Flow rate of release	L/s	-	90		-	Daily upon release
	pH	pH units	6	-		8.5	
	Total Residual Chlorine	mg/L	-	-		0.5	
	Total Suspended Solids	mg/L	-	-		55	
	Ammonia	µg/L	-	-		20	
	Dissolved Oxygen	mg/L	2	-		-	
	Electrical Conductivity	µS/cm			1600		
	E. coli	cfu/100mL	-	-		10	
	Total Nitrogen	mg/L	-	-		5	
	Total Phosphorous	mg/L	-	-		5	
	BOD5	mg/L	-	-		20	Upon release, and weekly thereafter

Associated monitoring requirements

1. Releases to **waters** are only permitted where the receiving **waters** of Grosvenor Creek have a flow rate of at least 8611 L/s.
2. Monitoring may be undertaken by in situ testing for the following quality characteristics: pH, Total Residual Chlorine, Total Suspended Solids, Ammonia, Dissolved Oxygen, and Electrical Conductivity. Where in situ testing is undertaken for a quality characteristic, at least one monitoring event per release must be undertaken by a NATA accredited laboratory. Where release events exceed one week in duration, least one monitoring event per week for the release must be undertaken by a NATA accredited laboratory.
3. Multiple release events separated in time by less than seven days between consecutive releases are considered to be a single release.
4. Monitoring must be undertaken during a release.
5. Samples must be representative of the release.
6. All monitoring devices must be effectively calibrated and maintained.

	7. Water quality monitoring must be in accordance with the methods prescribed in the current edition of the **administering authority's** Monitoring and Sampling Manual. 8. Indicators for TN and TP must be done as 24 hour composite samples.
Agency Interest: Dams	
Condition number	**Condition**
7-D01	The **holder** of this permit must ensure that each **dam** is designed, **constructed**, operated and maintained in accordance with accepted engineering standards and is fit for the purpose for which it is intended.
7-D02	The condition of **dams** must be monitored for early signs of loss of structural or hydraulic integrity, based on the advice of a **suitably qualified and experienced person**. The methods of monitoring and frequency of monitoring shall be as **assessed** by that **suitably qualified and experienced person**.
7-D03	In the event of early signs of loss of structural or hydraulic integrity, the **holder** of this permit must immediately take action to prevent or minimise any actual or potential environmental harm, and report in writing any findings and actions taken to the **administering authority** within twenty-eight (28) days of that event.
7-D04	The **holder** of this permit must not abandon any **dam** but must decommission each **dam** such that ongoing environmental harm is prevented.
7-D05	As a minimum, decommissioning must be conducted such that each **dam** is: (a) either: i. a stable landform, that no longer contains flowable substances, or ii. approved or authorised under relevant legislation for a beneficial use, or iii. a void authorised by the **administering authority** to remain after decommissioning; and (b) compliant with the rehabilitation requirements of this permit.
7-D06	**Regulated Dams - Location and basic specifications** The following are the only regulated **dams** authorised under this environmental authority, and those **dams** are to be located within the control points defined in *Table 4.7 – Location of regulated **dams***.

Table 7.4 – Location of regulated dams

Name of regulated dam	Easting (GDA94)	Northing (GDA94)
Mo-ESP1	5342.07	5145.62
	5711.86	5142.37
	5716.86	5078.85
	5338.94	5077.90
Mo-ESP2	5338.94	5077.90
	5716.86	5078.85
	5724.10	4995.10
	5330.30	4851.90
Mo-OSD	5050.50	5137.60
	5155.40	5137.60

		5155.40	5075.20
		5050.50	5072.20

7-D07

The following are the only regulated **dams** authorised under this environmental authority, and those **dams** are to accord with the basic specifications in *Table 7.5 – Basic specification of regulated dams*.

Table 7.5 – Basic specification of regulated dams

Name of regulated dam	Surface area of dam at crest (ha)	Volume at dam crest (ML)	Depth of dam at dam crest (m)	Purpose of dam
Mo-ESP1	7.79	144.8	4.54	Treated effluent storage
Mo-ESP2				
Mo-OSD	0.49	5.7	5.7	Overflow storage

7-D08

The following are the only regulated **dams** authorised under this environmental authority, and those **dams** are to accord with the hydraulic specifications in *Table 7.6 – Hydraulic performance of regulated dams*.

Table 7.6 – Hydraulic performance of regulated dams

Regulated dam	Design storage allowance volume (ML) below spillway	Spillway or protection critical design event	Mandatory reporting level (mAHD)	Extreme Storm Storage volume (ML) below spillway
Mo-ESP1	144.8	**AEP** 1 in 10,000	232.19	49.1
Mo-ESP2				
Mo-OSD	5.7	To be provided in accordance with condition 8-D14.	To be provided in accordance with condition 8-D14.	To be provided in accordance with condition 8-D14.

*to be provided with all submitted **design plans** in accordance with condition 8-D14.

7-D09

Certification and operation
Documentation required by the conditions in this schedule must be kept available for inspection by the regulating authority for a period of five (5) years after the conclusion of the environmentally relevant activity in respect of which this permit has been granted.

7-D10

The **holder** of this permit must not commence **construction** of a regulated **dam** unless:

(a) the **holder** has submitted to the **administering authority** two copies of a **design plan**, together with the **certification** of a **suitably qualified and experienced person** that the design of the regulated **dam** will deliver the performance stated in the **design plan** and that it will be compliant in all respects with this permit; and

(b) the **'Spillway** or Protection Critical Design Event' and **'Mandatory Reporting Level'** details to complete *Table 7.6 – Hydraulic performance of regulated dams*; and

	(c) at least twenty (20) business days has passed since the receipt of those documents, or the **administering authority** notifies the **holder** that a **design plan** and **certification**, has been received.
7-D11	For existing **dams** that were **constructed** prior to the issue of this permit, the **holder** must by 26 November 2010: (a) submitted to the **administering authority** two copies of a **design plan**, together with the **certification** of a **suitably qualified and experienced person** that the design of the regulated **dam** will deliver the performance stated in the **design plan** and that it will be compliant in all respects with this permit; and (b) the **'Spillway** or Protection Critical Design Event' and **'Mandatory Reporting Level'** details to complete *Table 7.6 - Hydraulic performance of regulated dams*.
7-D12	Each **design plan** for a regulated **dam** under this authority must consider the likely outcomes for **releases** to the environment using estimates of likely **contaminant** concentrations in using data from contact testing, output from modelling on **site** and modelling for flows in the nearby **watercourses**.
7-D13	The permit **holder** is required to adjust the operating levels of the waste water storage **dam** to prevent **releases** to an appropriate **Annual Exceedence Probability** (**AEP**) standard not exceeding 0.01 over the operating life.
7-D14	When **construction** or modification of any regulated **dam** is complete, the **holder** of this permit must submit to the **administering authority** two copies of a set of 'as **constructed**' drawings, together with the **certification** of a **suitably qualified and experienced person** that the **dam** 'as **constructed**' will deliver the performance stated in the **design plan** and that it will be compliant in all respects with this permit.
7-D15	The **holder** of this permit must ensure that there is always a current **operational plan** for each regulated **dam**, which may form part of other plans required by legislation.
7-D16	The **operational plan** shall at least cover all matters relevant to the **operation** and maintenance of the regulated **dam** so that it is compliant in all respects with this permit.
7-D17	The **holder** of this permit must ensure that, where a current **operational plan** covers decommissioning and rehabilitation, the operation plan is consistent with the objectives in any **design plan** for the **dam**.
7-D18	The **holder** of this permit must notify the **administering authority** immediately of the level in any regulated **dam** reaching the **mandatory reporting level** (**MRL**), and confirm in writing within seven (7) days.
7-D19	**Annual Inspection and Report** The **holder** of this permit must arrange for each regulated **dam** to be inspected annually by a **suitably qualified and experienced person** in accordance with the following conditions.
7-D20	At each annual inspection, the condition of each regulated **dam** must be **assessed**, including the structural, geotechnical and hydraulic adequacy of the **dam** and the adequacy of the **works** with respect to **dam** safety, and any recommended actions conveyed immediately to the **holder** of this permit.

7-D21	The **holder** of this permit must immediately act upon recommendations arising from an annual inspection on condition and adequacy of a **dam**.
7-D22	At each annual inspection, the adequacy of the available storage against the **design storage allowance** specified must be **assessed** and, if a **mandatory reporting level** is required, it must be determined and marked on each regulated **dam**.
7-D23	A final **assessment** of adequacy of available storage in each regulated **dam** must be based on a **dam** level observed within the month of October, accepted as valid by the **suitably qualified and experienced person**, and resulting in an estimate of the level in that **dam** as at 1 November.
7-D24	For each annual inspection, two copies of a report **certified** by the **suitably qualified and experienced person**, including any recommended actions to be taken to ensure the integrity of each regulated **dam**, must be provided to the **administering authority** by 1 December.

Definitions for Parts 1-7

Key terms and/or phrases used in this document are defined in this section and **bolded** throughout this document. Applicants should note that where a term is not defined, the definition in the *Environmental Protection Act 1994*, its regulations or environmental protection policies must be used. If a word remains undefined it has its ordinary meaning.

24 hour storm event with an average recurrence interval of 1 in 10 years means the maximum rainfall depth from a 24 hour duration precipitation event with an average recurrence interval of once in 10 years. *For example, an Intensity-Frequency-Duration table for a 24 hour duration event with an average recurrence interval of 1 in 10 years, identifies a rainfall intensity of 8.2mm/hour. The rainfall depth for this event is therefore 24 hour x 8.2mm/hour = 196.8mm.*

Activity means the environmentally relevant activities, whether resource activities or prescribed activities, to which the environmental authority relates.

Administering authority means the Department of Environment and Science or its successor or predecessors.

Annual exceedance probability or AEP the probability that at least one event in excess of a particular magnitude will occur in any given year.

Appropriately qualified person(s) means a person or persons who has professional qualifications, training, skills and experience relevant to the EA requirements and can give authoritative assessment, advice and analysis in relation to the EA requirements using the relevant protocols, standards, methods or literature.

Assessed or **assessment** by a **suitably qualified and experienced person** in relation to a consequence assessment of a **dam**, means that a statutory declaration has been made by that person and, when taken together with any attached or appended documents referenced in that declaration, all of the following aspects are addressed and are sufficient to allow an independent audit of the assessment:

(a) exactly what has been assessed and the precise nature of that determination;
(b) the relevant legislative, regulatory and technical criteria on which the assessment has been based;
(c) the relevant data and facts on which the assessment has been based, the source of that material, and the efforts made to obtain all relevant data and facts; and
(d) the reasoning on which the assessment has been based using the relevant data and facts, and the relevant criteria.

Background means noise, measured in the absence of the noise under investigation, as L A90,T being the A-weighted sound pressure level exceeded for 90 per cent of the time period of not less than 15 minutes, using Fast response.

BOD5 means the 5 day biochemical oxygen demand determined using standard tests (e.g. those used by **NATA** laboratories). This test is not inhibited for nitrification, otherwise would be referred to as “carbonaceous” BOD.

Boundary means within one metre of the cadastral boundary of the site.

Certification means assessment and approval must be undertaken by a **suitably qualified and experienced person** in relation to any assessment or documentation required by this Manual, including **design plans**, ‘as constructed’ drawings and specifications, construction, operation or an annual report regarding regulated structures, undertaken in accordance with the Board of Professional Engineers of Queensland Policy Certification by RPEQs (ID: 1.4 (2A)).

Certifying, **certify or certified** have a corresponding meaning as ‘certification’.

Commercial place means a place used as a workplace, an office or for business or commercial purposes and includes a place within the curtilage of such a place reasonably used by persons at that place.

Construction or constructed in relation to a **dam** includes building a new **dam** and modifying or lifting an existing **dam**, but does not include investigations and testing necessary for the purpose of preparing a **design plan**.

Dam means a land-based structure or a void that contains, diverts or controls flowable substances, and includes any substances that are thereby contained, diverted or controlled by that land-based structure or void and associated works.

Dam crest volume means the volume of material (liquids and/or solids) that could be within the walls of a dam at any time when the upper level of that material is at the crest level of that dam. That is, the instantaneous maximum volume within the walls, without regard to flows entering or leaving (for example, via **spillway**).

Day means any 24 hour period.

Design plan is a document setting out how all identified consequence scenarios are addressed in the planned design and operation of a regulated structure.

Design storage allowance or DSA means an available volume, estimated in accordance with the *Manual for assessing consequence categories and hydraulic performance of structures (ESR/2016/1933)* published by the administering authority, must be provided in a dam as at 1 November each year in order to prevent a discharge from that dam to an **annual exceedance probability** (AEP) specified in that Manual.

Disturbed areas includes areas:

1. that are susceptible to erosion;
2. that are contaminated by the **activity**; and/or
3. upon which stockpiles of soil or other materials are located.

Emergency action plan means documentation forming part of the **operational plan** held by the **holder** or a nominated responsible officer, that identifies emergency conditions that sets out procedures and actions that will be followed and taken by the dam owner and operating personnel in the event of an emergency. The actions are to minimise the risk and consequences of failure, and ensure timely warning to affected persons and the implementation of protection measures. The plan must require dam owners to annually review and update contact information where required.

Environmental nuisance as defined under Chapter 1 of the *Environmental Protection Act 1994.*

Environmental value as defined under Chapter 1 of the *Environmental Protection Act 1994.*

Extreme Storm Storage – means a storm storage allowance determined in accordance with the criteria in the *Manual for assessing consequence categories and hydraulic performance of structures (ESR/2016/1933)* published by the administering authority.

Groundwater means water that occurs naturally in, or is introduced artificially into, an aquifer.

Groundwater monitoring system means a system of groundwater monitoring devices, such as monitoring bores, used to provide data in respect to the level and quality of groundwater in the uppermost aquifer where the location of the groundwater monitoring devices is such that comparisons of groundwater quality and groundwater level can be made between groundwater flowing from beneath the site (down-gradient flow) of the **activity** and groundwater flowing towards the site of the **activity** (up-gradient flow).

Holder means:

(a) where this document is an environmental authority, any person who is the holder of, or is acting under, that environmental authority; or
(b) where this document is a development approval, any person who is the registered operator for that development approval.

$L_{A1, adj, 10 mins}$ means the A-weighted sound pressure level, (adjusted for tonal character and impulsiveness of the sound) exceeded for 1% of any 10 minute measurement period, using Fast response.

$L_{A10, adj, 10 mins}$ means the A-weighted sound pressure level, (adjusted for tonal character and impulsiveness of the sound) exceeded for 10% of any 10 minute measurement period, using Fast response.

$L_{A, max adj T}$ means the average maximum A-weighted sound pressure level, adjusted for noise character and measured over any 10 minute period, using Fast response.

Liquid means any substance that:

1. has an angle of repose of less than five degrees; or
2. becomes free flowing at or below 60 degrees Celsius or when it is transported; or
3. is not generally capable of being picked up by a spade or shovel.

Mandatory reporting level or MRL means a warning and reporting level determined in accordance with the criteria in the *Manual for assessing consequence categories and hydraulic performance of structures (ESR/2016/1933)* published by the administering authority.

Measures has the broadest interpretation and includes plant, equipment, physical objects, monitoring, procedures, actions, directions and competency.

Median means the middle value, where half the data are smaller and half the data are larger. If the number of samples is even, the median is the arithmetic average of the two middle values. This applies to data obtained from one release event, e.g. if a release occurs over a period of 3 days, the median is applied to the monitoring obtained over those three days.

NATA means National Association of Testing Authorities.

Operational plan includes:

(a) normal operating procedures and rules (including clear documentation and definition of process inputs in the DSA);
(b) contingency and **emergency action plans** including operating procedures designed to avoid and/or minimise environmental impacts including threats to human life resulting from any overtopping or loss of structural integrity of the regulated structure.

Receiving environment monitoring program means a monitoring program designed to monitor and assess the potential impacts of controlled and/or uncontrolled releases of contaminants to the environment from the **activity**.

Records include breach notifications, written procedures, analysis results, monitoring reports and monitoring programs required under a condition of this authority.

Release of a contaminant into the environment means to:

(e) deposit, discharge, emit or disturb the contaminant
(f) cause or allow the contaminant to be deposited, discharged, emitted or disturbed
(g) fail to prevent the contaminant from being deposited, discharged emitted or disturbed
(h) allow the contaminant to escape

(i) fail to prevent the contaminant from escaping.

Sensitive place includes the following and includes a place within the curtilage of such a place reasonably used by persons at that place:

1. a dwelling, residential allotment, mobile home or caravan park, residential marina or other residential premises; or
2. a motel, hotel or hostel; or
3. a kindergarten, school, university or other educational institution; or
4. a medical centre or hospital; or
5. a protected area under the *Nature Conservation Act 1992*, the *Marine Parks Act 2004* or a World Heritage Area; or
6. a public thoroughfare, park or gardens; or
7. for noise, a place defined as a sensitive receptor for the purposes of the Environmental Protection (Noise) Policy 2008.

Spillway means a weir, channel, conduit, tunnel, gate or other structure designed to permit discharges form the dam, normally under flood conditions or in anticipation of flood conditions.

Suitably qualified and experienced person in relation to regulated structures means a person who is a Registered Professional Engineer of Queensland (RPEQ) under the provisions of the *Professional Engineers Act 2002*, and has demonstrated competency and relevant experience:

- for regulated dams, an RPEQ who is a civil engineer with the required qualifications in dam safety and dam design
- for regulated levees, an RPEQ who is a civil engineer with the required qualifications in the design of flood protection embankments.

Note: It is permissible that a suitably qualified and experienced person obtain subsidiary certification from an RPEQ who has demonstrated competence and relevant experience in either geomechanics, hydraulic design or engineering hydrology.

Total Nitrogen (TN) means the sum of Organic Nitrogen, Ammonia Nitrogen, Nitrite plus Nitrate Nitrogen, expressed as mg/L as Nitrogen. This includes both the inorganic and organic fraction of nitrogen.

Total Phosphorus (TP) means the sum of the reactive phosphorus, acid-hydrolysable phosphorus and organic phosphorus, as mg/L of Phosphorus. This includes both the inorganic and organic fraction of phosphorus**.**

Watercourse has the meaning in Schedule 4 of the *Environmental Protection Act 1994* and means:

1. a river, creek or stream in which water flows permanently or intermittently—
   (a) in a natural channel, whether artificially improved or not; or
   (b) in an artificial channel that has changed the course of the watercourse.
2. Watercourse includes the bed and banks and any other element of a river, creek or stream confining or containing water.

Waters includes river, stream, lake, lagoon, pond, swamp, wetland, unconfined surface water, unconfined water, natural or artificial watercourse, bed and bank of any waters, dams, non-tidal or tidal waters (including the sea), stormwater channel, stormwater drain, roadside gutter, stormwater run-off, and **groundwater** and any part thereof.

You means the **holder** of the environmental authority.

Part 8 – Waste, Former NM0140

Environmentally relevant activities	Locations
ERA 60 Waste disposal, Threshold 2(b) operating a facility for disposing of, in a year, 2000-5000t of waste mentioned in subsection (1)(b)	Clermont Waste Management Facility: 38 Turama Rd, Clermont; Lot 2 on SP231842
ERA 56 Regulated waste storage	Clermont Waste Management Facility: 38 Turama Rd, Clermont; Lot 2 on SP231842 Moranbah Works depot, Grosvenor Goonyella Rd Moranbah; Reserve 7 Lot 2 Plan GV321 Spoonbill Road, Clermont; Lot 228 CLM 63

The environmentally relevant activities conducted at the locations as described above must be conducted in accordance with the following site specific conditions of approval:

Schedule A: General Conditions	
Condition number	**Condition**
8-A01	**Access to Copy of Environmental Authority** A copy of this environmental authority must be kept in a location readily accessible to personnel carrying out the activity.
8-A02	**Records** Any record or document required to be kept by a condition of this environmental authority must be kept at the licensed place for a period of at least five years and be available for examination by an authorised person. For daily and weekly records, the record retention requirements of this condition will be satisfied if any daily and weekly records are kept for a period of at least three (3) years and these records are then kept in the form of annual summaries after that period.
8-A03	**Alterations** No change, replacement or operation of any plant or equipment is permitted if the change, replacement or operation of the plant or equipment increases, or is likely to substantially increase, the risk of environmental harm above that expressly provided by this environmental authority. An example of a substantial increase in the risk of environmental harm is an increase of 10% or more in the quantity of the contaminant to be released into the environment.
8-A04	**Monitoring and Measurements** All determinations of the quality of contaminants released to the environment and all measurement and reporting of noise levels that are required by this environmental authority must be undertaken by a person or body possessing appropriate experience and qualifications to perform the required determinations and the required measurements.
8-A05	All instruments and devices used for the measurement or monitoring of any parameter under any condition of this environmental authority must be calibrated, and appropriately operated and maintained.

8-A06	**Integrated Environmental Management System (IEMS)** The holder of this environmental authority must: (a) develop and implement an Integrated Environmental Management System which provides for the following functions: (i) the monitoring of releases of contaminants into the environment and an environmental assessment of the releases; and (ii) staff training and awareness of environmental issues; and (iii) the conduct of environmental and energy audits; and (iv) waste prevention, treatment and disposal; and (b) by the First Annual Return, lodge a detailed description of the Integrated Environmental Management System and its documentation with the administering authority for its review and comment; and (c) have due regard to that comment in the finalisation of the Integrated Environmental Management System.
8-A07	A copy of the Integrated Environmental Management System must be kept in a location readily accessible to personnel carrying out the activity
Schedule B: Noise	
Condition number	**Condition**
8-B01	**Emission of Noise** The emission of noise from the licensed activities shall conform to the contents of the Environmental Protection (Noise) Policy 1997.
Schedule C: Waste Management	
Condition number	**Condition**
8-C01	**General** The holder of this environmental authority must not: (i) allow waste to burn or be burned at or on the licensed place; nor (ii) remove waste from the licensed place and burn such waste elsewhere.
8-C02	**Notification of Improper Disposal of Regulated Waste** If the holder of this environmental authority becomes aware that a person has removed regulated waste from the licensed place and disposed of the regulated waste in a manner which is not authorised by this environmental authority or improper or unlawful, then the holder of this environmental authority must, as soon as practicable, notify the administering authority of all relevant facts, matters and circumstances known concerning the disposal.
Schedule D: Monitoring and Reporting	
Condition number	**Condition**
8-D01	**Complaint Recording**

	All complaints received by the holder of this environmental authority relating to releases of contaminants from operations at the licensed place must be recorded and kept with the following details: (a) time, date and nature of complaint; (b) type of communication (telephone, letter, personal etc.); (c) name, contact address and contact telephone number of complainant (Note: if the complainant does not wish to be identified then "Not identified" is to be recorded); (d) response and investigation undertaken as a result of the complaint; (e) name of person responsible for investigating complaint; and (f) action taken as a result of the complaint investigation and signature of responsible person.
8-D02	**Report Submission** The holder of this environmental authority must ensure that the results of all monitoring performed in accordance with this environmental authority for the period covered by the return are submitted with the Annual Return.
8-D03	**Incident Recording** A record must be maintained of at least the following events: (a) the time, date and duration of equipment malfunctions where the failure of the equipment resulted in the release of contaminants reasonably likely to cause environmental harm; (b) any uncontrolled release of contaminants reasonably likely to cause environmental harm and (c) any emergency involving the release of contaminants reasonably likely to cause material or serious environmental harm requiring the use of fire-fighting equipment.
8-D04	**Notification of Emergencies and Incidents** Where the holder of this environmental authority has not given notification to the administering authority under section 37 of the *Environmental Protection Act 1994*, as soon as practicable after becoming aware of any emergency or incident which results in the release of contaminants not in accordance, or reasonably expected to be not in accordance with the conditions of this environmental authority, the holder of this environmental authority must notify the administering authority of the release by telephone or facsimile.
8-D05	Where the holder of this environmental authority has not given notification to the administering authority under section 37 of the *Environmental Protection Act 1994*, the notification of emergencies or incidents as required by condition number (8-D04) must include but not be limited to the following: (a) the holder of the environmental authority; (b) the location of the emergency or incident; (c) the number of the environmental authority; (d) the name and telephone number of the designated contact person; (e) the time of the release; (f) the time the holder of the environmental authority became aware of the release; (g) the suspected cause of the release;

	(h) the environmental harm and or environmental nuisance caused, threatened, or to be caused by the release; and (i) actions taken to prevent further any release and mitigate any environmental harm and or environmental nuisance caused by the release.
8-D06	Where the holder of this environmental authority has not given notification to the administering authority under section 37 of the *Environmental Protection Act 1994*, not more than 14 days following the initial notification of an emergency or incident, the holder of the environmental authority must provide written advice of the information supplied in accordance with condition number (8-D05) in addition to: (a) proposed actions to prevent a recurrence of the emergency or incident; (b) outcomes of actions taken at the time to prevent or minimise environmental harm and or environmental nuisance.
8-D07	**Exception Reporting** The holder of this environmental authority must notify the administering authority in writing within 28 days of completion of analysis of any result of a monitoring program required by a condition of this environmental authority which indicates an exceedance of any limit specified in this environmental authority.
8-D08	The written notification required by condition number (8-D07) above must include: (a) The full analysis results, and (b) Details of investigation or corrective actions taken, and (c) Any subsequent analysis.
Schedule F: General Waste Disposal Facility	
Condition number	**Condition**
8-F01	**Design and Operating Criteria** The waste accepted at the landfill facility must be in accordance with the Council's Waste Acceptance Criteria.
8-F02	An area must be set aside for segregation and storage of recyclable solid wastes.
8-F03	Exposed wastes must be confined to the working face of the landfill units and minimised.
8-F04	No waste must be deposited beyond the boundaries of the landfill units.
8-F05	Waste deposited within the landfill facility must be evenly and properly consolidated by mechanical plant at the end of each week.
8-F06	Putrescible wastes or domestic wastes must be deposited at least 2.0 meters above the highest regional water table or as otherwise approved based on the liner design and groundwater monitoring network.
8-F07	Deposited waste must be covered with 0.20 meter thick earthen material or other dense and incombustible alternative material of a thickness and nature acceptable to the administering authority, at the end of each week or at more frequent intervals if necessary, so that no putrescible wastes are exposed.
8-F08	Adequate cover material for at least two weeks operation must be stored and be readily available on the licensed site.

8-F09	The licensed premises must be appropriately fenced to restrict unauthorised access to the site, and provide litter and stock control.
8-F10	The fence around the site must be maintained in good repair. A regular program of litter collection must be conducted to ensure that the site, fence and the surrounds of the site are kept in a tidy condition.
8-F11	The holder of this environmental authority must prominently display on the licensed site appropriate signs with the following information: • types of waste which must be deposited at the site and a contact telephone number for information on alternative disposal options; • prominent list of materials acceptable for recycling and the location of them to be deposited on site; • contact telephone number for information and complaints; • a warning sign indicating that unlawful disposal and unauthorised scavenging is prohibited; • a warning sign indicating that open burning is prohibited.
8-F12	**Fire prevention** The holder of this environmental authority must ensure that the fire-fighting equipment is readily accessible at all times.
8-F13	A fire break must be provided and maintained in consultation with the Regional Fire Commander.
8-F14	**Public Health Issues** The holder of this environmental authority must take all practical measures to ensure that the environmentally relevant activity is conducted at all times in a nuisance free manner, particularly regarding fly breeding, mosquito breeding and rat harbourage and breeding.
8-F15	A program for the monitoring and control of rodents and insect pests must be established and maintained to the satisfaction of the administering authority.
8-F16	**Nuisance** No release of contaminants, including but not limited to odour, dust, smoke, fume, particulate, and aerosols is to cause or be likely to cause an environmental nuisance beyond the boundaries of the licensed place.
8-F17	**Water Pollution Control** Contaminants must not be directly or indirectly released from the licensed place to any waters, including groundwater, or bed and banks of any waters.
8-F18	Leachate must not be permitted to discharge beyond the boundaries of the licensed place.
8-F19	Diversion drainage structures must be in place to divert stormwater flows away from disposal areas.
8-F20	Stormwater runoff polluted by waste or leachate must not be permitted to discharge beyond the boundaries of the licensed place.
8-F21	By the First Annual Return, the holder of this environmental authority must submit to the administering authority the Management Plan to address the need for leachate management.
8-F22	**Site Rehabilitation**

	At cessation of waste disposal operations of a stage of the licensed place, a final cover consisting of at least 500 millimeters depth of compacted clean earth must be placed over the completed area.
8-F23	The final surface of any completed area of the licensed place must, after covering as specified in conditions above, be graded, drained and vegetated in such a manner as to minimise erosion and to prevent ponding of stormwater.
8-F24	Erosion and sediment control structures must be maintained at all times during the period rehabilitation and checked, repaired or replaced as required after each rain event.
8-F25	**Closure and Post-closure Care** The holder of the environmental authority must conduct post closure care of any landfill unit for 30 years or until it can be demonstrated to the administering authority that the site is geotechnically stable and will not release contaminants to the environment. Such care would compromise: (i) maintaining the integrity and effectiveness of any final cover; (ii) maintaining and operating the leachate collection system; (iii) monitoring the groundwater water quality.
8-F26	The holder of this environmental authority must: (i) develop and implement a landfill unit rehabilitation plan in accordance with the requirements referred to in condition (8-F25); (ii) lodge with the administering authority the landfill unit rehabilitation plan proposal at least 12 months before the anticipated final receipt of wastes in the landfill unit for its review and comment; (iii) have due regard to this comment in the finalisation of the landfill unit rehabilitation plan.
8-F27	The holder of this environmental authority must begin closure activities of any landfill unit no later than 28 days after the date on which landfill unit receives the final recorded receipt of wastes.
8-F28	**Groundwater Monitoring** A groundwater monitoring system must be installed for any landfill unit. The system must include a sufficient number of wells installed at locations and depths which yield representative groundwater samples from the uppermost aquifer that establish: (i) background groundwater quality in hydraulically up-gradient or background well(s) that have not been affected by any potential leakage of contaminants to groundwater; (ii) quality of groundwater down-gradient of any potential leakage of contaminants to groundwater.
8-F29	Locations referred to in condition (8-F28) for groundwater monitoring facilities must be given with reference to horizontal co-ordinates of such facilities accurate to 1.0 meter.
8-F30	The point(s) of compliance referred to in condition (8-F28) for the groundwater monitoring system(s) must be situated not more than 150 meters from any landfill unit or the boundary of the landfill facility whichever is closest.

Schedule H: Regulated Waste Storage	
Condition number	**Condition**
8-H01	**Bunding** The regulated waste storage must be bunded so that the capacity of the bund is sufficient to contain at least 25% of the maximum design storage volume within the bund.
8-H02	All bunding must be constructed of materials which are impervious to the materials stored or likely to come into contact with the bund. The base and walls of all bunded areas must be maintained free from gaps and cracks.
8-H03	Drum storage of regulated waste must be within roofed areas.
8-H04	For the purposes of this licence, stormwater and liquid collected within the bunded areas must be regarded as contaminated.
8-H05	No wastewater collected within bunded areas is to be discharged to the stormwater drainage system.
8-H06	Stormwater run-off from adjacent land uses must not be permitted to enter the contaminated area.

Part 9 – Waste, Former NM0105

Environmentally relevant activities	Locations
ERA 60 Waste disposal, Threshold 2(b) operating a facility for disposing of, in a year, 2000-5000t of waste mentioned in subsection (1)(b)	Nebo Waste Management Facility; 17914 Peak Downs Highway, Nebo; Lot 98 on SP159584 Glenden Waste Management Facility: 412 Ewan Drive, Glenden; Lot 10 Plan HLN205

The environmentally relevant activities conducted at the locations as described above must be conducted in accordance with the following site specific conditions of approval:

Schedule A: General Conditions	
Condition number	**Condition**
9-A01	**Access to Copy of Environmental Authority** A copy of this environmental authority must be kept in a location readily accessible to personnel carrying out the activity.
9-A02	**Records** Any record or document required to be kept by a condition of this environmental authority must be kept at the licensed place for a period of at least five years and be available for examination by an authorised person. The record retention requirements of this condition will be satisfied if any daily and weekly records are kept for a period of at least three (3) years and these records are then kept in the form of annual summaries after that period.
9-A03	**Alterations** No change, replacement or operation of any plant or equipment is permitted if the change, replacement or operation of the plant or equipment increases, or is likely to substantially increase, the risk of environmental harm above that expressly provided by this environmental authority. An example of a substantial increase in the risk of environmental harm is an increase of 10% or more in the quantity of the contaminant to be released into the environment.
9-A04	**Monitoring and Measurements** All determinations of the quality of contaminants released to the environment and all measurement and reporting of noise levels that are required by this environmental authority must be undertaken by a person or body possessing appropriate experience and qualifications to perform the required determinations and the required measurements.
9-A05	All instruments and devices used for the measurement or monitoring of any parameter under any condition of this environmental authority must be calibrated, and appropriately operated and maintained.
9-A06	**Integrated Environmental Management System (IEMS)** The Integrated Environmental Management System submitted on 10 January 2000 by the holder of this environmental authority must be implemented ensuring that the IEMS provides for the following functions: (i) the monitoring of releases of contaminants into the environment, and

	(i) an environmental assessment of the impact of releases; and (ii) the management of the contamination of stormwater; and (iii) the maintenance of noise attenuation equipment; and (iv) waste prevention, treatment and disposal; and (v) the conduct of environmental and energy audits; and (vi) a program for continuous improvement; and (vii) staff training and awareness of environmental issues; and (viii) reporting arrangements on the effectiveness of the environmental management of the activities; and (ix) complaint and incident recording; and (x) notification of emergencies, incidents and exceptions.
9-A07	The management of the contamination of stormwater required by condition (9-A6)(iii) must include, as a minimum: a) a detailed plan of the licensed sites showing all stormwater flows and discharge points; and b) standards for bunding of fuel and chemical storages and transfer lines; and c) procedures and mechanisms for avoidance and minimisation of contaminated stormwater; and d) procedures for minimising and for cleaning up spillages and leaks; and e) procedures and mechanisms for treatment and disposal of contaminated stormwater
Schedule B: Noise	
Condition number	**Condition**
9-B01	**Emission of Noise** In the event the holder of this environmental authority receives a noise complaint associated with carrying out the environmentally relevant activities, the holder must, within a reasonable period of time, investigate the complaint and take any actions necessary to satisfactorily resolve the complaint including the use of appropriate dispute resolution if required.
9-B02	**Noise Monitoring** Monitoring must be undertaken to investigate any complaint of noise annoyance upon receipt of a written request from the administering authority to carry out such monitoring.
9-A05	All instruments and devices used for the measurement or monitoring of any parameter under any condition of this environmental authority must be calibrated, and appropriately operated and maintained.
Schedule C: Solid Waste Management	
Condition number	**Condition**
9-C01	**General** The holder of this environmental authority must not: (i) allow waste to burn or be burned at or on the licensed place; nor (ii) remove waste from the licensed place and burn such waste elsewhere.

9-C02	**Off Site Movement** Where regulated waste is removed from the licensed place (other than by a release as permitted under another schedule of this environmental authority), the holder of this environmental authority must monitor and keep records of the following: (a) the date, quantity and type of waste removed; and (b) name of the waste transporter and/or disposal operator that removed the waste; and (c) the intended treatment/disposal destination of the waste.
9-C03	**Notification of Improper Disposal Of Regulated Waste** If the holder of this environmental authority becomes aware that a person has removed regulated waste from the licensed place and disposed of the regulated waste in a manner which is not authorised by this environmental authority or improper or unlawful, then the holder of this environmental authority must, as soon as practicable, notify the administering authority of all relevant facts, matters and circumstances known concerning the disposal.
Schedule D: Monitoring and Reporting	
Condition number	**Condition**
9-D01	**General** The holder of this environmental authority must not: (i) allow waste to burn or be burned at or on the licensed place; nor (ii) remove waste from the licensed place and burn such waste elsewhere.
9-D02	**Report Submission** The holder of this environmental authority must ensure that the results of all monitoring performed in accordance with this environmental authority for the period covered by the return are submitted with the Annual Return.
9-D03	**Incident Recording** A record must be maintained of at least the following events: (i) the time, date and duration of equipment malfunctions where the failure of the equipment resulted in the release of contaminants reasonably likely to cause environmental harm; (ii) any uncontrolled release of contaminants reasonably likely to cause environmental harm and (iii) any emergency involving the release of contaminants reasonably likely to cause material or serious environmental harm requiring the use of fire-fighting equipment.
9-D04	**Notification of Emergencies and Incidents** Where the licensee has not given notification to the administering authority under section 37 of the *Environmental Protection Act 1994*, as soon as practicable after becoming aware of any emergency or incident which results in the release of contaminants not in accordance, or reasonably expected to be not in accordance with the conditions of this environmental authority, the holder of this environmental authority must notify the administering authority of the release by telephone or facsimile.

9-D05	Where the licensee has not given notification to the administering authority under section 37 of the *Environmental Protection Act 1994*, the notification of emergencies or incidents as required by condition number (9-D04) must include but not be limited to the following: The holder of the environmental authority; (a) the location of the emergency or incident; (b) the number of the environmental authority; (c) the name and telephone number of the designated contact person; (iv) the time of the release; (v) the time the holder of the environmental authority became aware of the release; (vi) the suspected cause of the release; (vii) the environmental harm and or environmental nuisance caused, threatened, or to be caused by the release; and (viii) actions taken to prevent further any release and mitigate any environmental harm and or environmental nuisance caused by the release.
9-D06	Where the licensee has not given notification to the administering authority under section 37 of the *Environmental Protection Act 1994*, not more than 14 days following the initial notification of an emergency or incident, the holder of the environmental authority must provide written advice of the information supplied in accordance with condition number (9-D05) in addition to: (i) proposed actions to prevent a recurrence of the emergency or incident; (ii) outcomes of actions taken at the time to prevent or minimise environmental harm and or environmental nuisance.
9-D07	**Exception Reporting** The holder of this environmental authority must notify the administering authority in writing of any monitoring result which indicates an exceedance of any licence limit within 28 days of completion of analysis.
9-D08	The written notification required by condition number (9-D07) above must include: (i) The full analysis results, and (ii) Details of investigation or corrective actions taken, and (iii) Any subsequent analysis.
Schedule G: General Waste Disposal Facility	
Condition number	**Condition**
9-G01	**Design and Operating Criteria** The waste accepted at the landfill facility must be in accordance with the Council's Waste Acceptance Criteria.
9-G02	No waste must be deposited beyond the boundaries of the landfill units.
9-G03	An area must be set aside for segregation and storage of recyclable wastes.
9-G04	Waste deposited within the landfill facility must be evenly and properly consolidated by mechanical plant at least once per week.
9-G05	The licensed premises must be appropriately fenced to restrict unauthorised access to the site, and provide litter and stock control.

9-G06	The holder of this environmental authority must prominently display on the licensed site appropriate signs with the following information: • types of waste which must be deposited at the site and a contact telephone number for information on alternative disposal options; • prominent list of materials acceptable for recycling and the location for them to be deposited on site; • contact telephone number for information and complaints; • a warning sign indicating that unlawful disposal and unauthorised scavenging is prohibited; • a warning sign indicating that open burning is prohibited.
9-G07	**Disposal Trench Management** The holder of this environmental authority must ensure that any active disposal trench is excavated into low permeability soils of sufficient thickness and appropriate characteristics to effectively attenuate landfill leachate percolating from the trench to an extent that the migration of landfill leachate to groundwater shall not cause environmental harm or environmental nuisance.
9-G08	All active waste disposal trenches must be constructed in such a manner that the floor of the trench is graded with a slope downward from the active tipping face to a sump to enable accumulation of contaminated stormwater to be removed during trench operation.
9-G09	The holder of this environmental authority must use temporary berms of low permeability material to minimise the exposure of waste deposited in active disposal trenches to rainwater which may accumulate in the trenches.
9-G10	No putrescible wastes shall be deposited of into water. Putrescible wastes or domestic wastes must be deposited at least 2.0 meters above the highest regional water table or as otherwise approved based on the liner design and groundwater monitoring network.
9-G11	Sufficient cover material for at least two weeks operation must be stored and be readily available at the licensed site.
9-G12	**Litter** The holder of this environmental authority must ensure that the movement of litter off the licensed place does not cause environmental harm or nuisance through the use of practicable and effective litter control measures and management practices. Such measures may include, but not be limited to, minimisation of the areas of uncovered wastes; frequent application of cover to deposited wastes; the use of relocatable litter screens around areas of waste deposition; the use of fixed litter control fencing around the site perimeter or other places; the implementation of regular litter collection programs that include cleaning of site perimeter fencing.
9-G13	**Fire Prevention and Control** The holder of this environmental authority must at all times maintain clear access for fire fighting vehicles and equipment.
9-G14	A fire break must be provided and maintained in consultation with the Regional Fire Commander.
9-G15	The holder of this environmental authority must act to ensure that any unauthorised fire on the licensed place is promptly extinguished.

9-G16	**Public Health Issues** The holder of this environmental authority must operate the licensed activity in such a manner that as far as is practical, fly and mosquito breeding and rat harbourage and breeding are minimised to ensure that the activity does not create a public health problem.
9-G17	The holder of this environmental authority must take all practical measures to ensure that the environmentally relevant activity is conducted at all times in a nuisance free manner, particularly regarding fly breeding, mosquito breeding and rat harbourage and breeding.
9-G18	The holder of this environmental authority must carry out any works required by the administering authority to prevent or abate any public health problem or nuisance which may arise as the result of the operation of the licensed place.
9-G19	**Bird and Animal Control** The holder of this environmental authority shall institute effective measures to prevent environmental harm or nuisance due to the congregation of birds at the licensed place.
9-G20	The holder of this environmental authority must also prevent the access of animals to deposited wastes. Such measures may include, but not be limited to minimisation of the areas of uncovered wastes; frequent application of cover to deposited wastes; and provision of animal proof fencing.
9-G21	**Stormwater Management** A system of suitable diversion drains or embankments must be constructed and maintained to divert surface waters away from any area of the licensed place where contact with wastes or contaminants may occur, including but not limited to: (a) active disposal trenches; and (b) areas used for the storage of wastes; and (c) areas previously used for waste disposal.
9-G22	During construction of each landfill trench, adequate silt fencing must be maintained downstream of disturbed areas to minimise sediment transport from the site.
9-G23	The cover material stockpile(s) located at the licensed place must be appropriately contoured to minimise surface erosion and sediment transport.
9-G24	Stormwater diversion drains must be installed upstream of areas to be disturbed prior to commencement of construction activities to divert uncontaminated stormwater away from disturbed areas and waste disposal areas.
9-G25	**Site Rehabilitation** At cessation of waste disposal operations of a stage of the licensed place, a final cover consisting of at least 500 millimetres depth of compacted clean earth must be placed over the completed area.
9-G26	The final surface of any completed area of the licensed place must, after covering as specified in conditions above, be graded, drained and vegetated in such a manner as to minimise erosion and to prevent ponding of stormwater.
9-G27	Erosion and sediment control structures must be maintained at all times during the period rehabilitation and checked, repaired or replaced as required after each rain event.
9-G28	**Closure and Post-closure Care**

	The holder of the environmental authority must conduct post closure care of any landfill unit for 30 years or until it can be demonstrated to the administering authority that the site is geotechnically stable and will not release contaminants to the environment. Such care would comprise: (i) maintaining the integrity and effectiveness of any final cover; (ii) maintaining and operating the leachate collection system; (iii) monitoring the groundwater water quality.
9-G29	The holder of this environmental authority must: (i) develop and implement a landfill unit rehabilitation plan in accordance with the requirements referred to in condition (9-G28); (ii) lodge with the administering authority the landfill unit rehabilitation plan proposal at least 12 months before the anticipated final receipt of wastes in the landfill unit for its review and comment; (iii) have due regard to this comment in the finalisation of the landfill unit rehabilitation plan.
9-G30	The holder of this environmental authority must begin closure activities of any landfill unit no later than 28 days after the date on which landfill unit receives the final recorded receipt of wastes.
9-G31	**Groundwater Monitoring** A groundwater monitoring system must be installed for any landfill unit. The system must include a sufficient number of wells installed at locations and depths which yield representative groundwater samples from the uppermost aquifer that establish: (i) background groundwater quality in hydraulically up-gradient or background well(s) that have not been affected by any potential leakage of contaminants to groundwater; (ii) quality of groundwater down-gradient of any potential leakage of contaminants to groundwater.
9-G32	Locations referred to in condition (9-G31) for groundwater monitoring facilities must be given with reference to horizontal co-ordinates of such facilities accurate to 1.0 metre.
9-G33	The point(s) of compliance referred to in condition (9-G31) for the groundwater monitoring system(s) must be situated not more than 150 metres from any landfill unit or the boundary of the landfill facility whichever is closest.
9-G34	The holder of the environmental authority must monitor quality of groundwater at least every 6 months to detect any possible release(s) of contaminants for at least the following water quality characteristics: 1. Ammonia (as N) 2. Bicarbonate (HCO3) 3. Calcium 4. Chloride 5. Iron (total) 6. Manganese (dissolved) 7. Nitrate (as N) 8. pH (field measured) 9. Potassium 10. Sodium

	11. Sulphate 12. Specific conductance 13. Total Organic Carbon (TOC) 14. Zinc
Schedule I: Definitions	
Condition number	**Condition**
2-I01	**Noise Definitions** "$L_{Amax\ adj,\ T}$" means the average maximum A-weighted sound pressure level, adjusted for noise character and measured over a time period of not less than 15 minutes, using Fast response.
2-I02	"Background noise level" means either: • $L_{A90,T}$ being the A-weighted sound pressure level exceeded for 90 percent of the time period of not less than 15 minutes, using Fast response, or • $L_{Abg,T}$ being the arithmetic average of the minimum readings measured in the absence of the noise under investigation during a representative time period of not less than 15 minutes, using Fast response.
2-I03	"$MaxL_{pA\ T}$" means the maximum A-weighted sound pressure level measured over a time period of not less than 15 minutes, using Fast response.
2-I04	"noise sensitive place" means - (a) a dwelling, mobile home or caravan park, residential marina or other residential premises; or (b) a motel, hotel or hostel; or (c) a kindergarten, school, university or other educational institution; or (d) a medical centre or hospital; or (e) a protected area; or (f) a public park or gardens.
2-I05	"commercial place" means a place used as an office or for business or commercial purposes.

Part 10 – Waste, Former NM0139

Environmentally relevant activities	Locations
ERA 60 Waste disposal, Threshold 2(a) operating a facility for disposing of, in a year, 50-2000t of waste mentioned in subsection (1)(b)	Carmila Waste Management Facility: 153 Carmila West Road, Carmila; Lot 80 Plan MC682 Middlemount Waste Management Facility: 60 Nolan Drive, Middlemount; Lot 49 Plan CNS281 Dysart Waste Management Facility: 7145 Dysart-Clermont Road, Dysart; Lot 1 on SP201845 St Lawrence Waste Management Facility: 402 St Lawrence Connection Road, St Lawrence; Lot 66 Plan MUR40149 Greenhill Waste Management Facility: 1026 Greenhill Road, Ilbilbie; Lot 68 Plan MC683

The environmentally relevant activities conducted at the locations as described above must be conducted in accordance with the following site specific conditions of approval:

Schedule A: General Conditions	
Condition number	**Condition**
10-A01	**Access to Copy of Environmental Authority** A copy of this environmental authority must be kept in a location readily accessible to personnel carrying out the activity.
10-A02	**Records** Any record or document required to be kept by a condition of this environmental authority must be kept at the licensed place for a period of at least five years and be available for examination by an authorised person. For daily and weekly records, the record retention requirements of this condition will be satisfied if any daily and weekly records are kept for a period of at least three (3) years and these records are then kept in the form of annual summaries after that period.
10-A03	**Alterations** No change, replacement or operation of any plant or equipment is permitted if the change, replacement or operation of the plant or equipment increases, or is likely to substantially increase, the risk of environmental harm above that expressly provided by this environmental authority. An example of a substantial increase in the risk of environmental harm is an increase of 10% or more in the quantity of the contaminant to be released into the environment.
10-A04	**Monitoring and Measurements** All determinations of the quality of contaminants released to the environment and all measurement and reporting of noise levels that are required by this environmental authority must be undertaken by a person or body possessing appropriate experience and qualifications to perform the required determinations and the required measurements.

10-A05	All instruments and devices used for the measurement or monitoring of any parameter under any condition of this environmental authority must be calibrated, and appropriately operated and maintained.
10-A06	**Integrated Environmental Management System (IEMS)** The Integrated Environmental Management System submitted by the holder of this environmental authority with the licence application is acknowledged by the **administering authority** as being a provisional IEMS only.
10-A07	The holder of this environmental authority must: (a) develop and implement an Integrated Environmental Management System which provides for the following functions: (i) the monitoring of releases of contaminants into the environment and an environmental assessment of the releases; and (ii) staff training and awareness of environmental issues; and (iii) the conduct of environmental and energy audits; and (iv) waste prevention, treatment and disposal; and (b) on or before the date of the first annual return lodge a detailed description of the Integrated Environmental Management System and its documentation with the **administering authority** for its review and comment; and (c) have due regard to that comment in the finalisation of the Integrated Environmental Management System.
10-A08	A copy of the Integrated Environmental Management System must be kept in a location readily accessible to personnel carrying out the activity.
Schedule B: Noise	
Condition number	**Condition**
10-B01	**Emission of Noise** The environmentally relevant activities must be carried out by such practicable means necessary to prevent the emission or likelihood of emission of noise that constitutes environmental nuisance.
Schedule C: Waste Management	
Condition number	**Condition**
10-C01	**General** The holder of this environmental authority must not: (i) allow waste to burn or be burned at or on the licensed place; nor (ii) remove waste from the licensed place and burn such waste elsewhere.
10-C02	**Notification of Improper Disposal Of Regulated Waste** If the holder of this environmental authority becomes aware that a person has removed regulated waste from the licensed place and disposed of the regulated waste in a manner which is not authorised by this environmental authority or improper or unlawful, then the holder of this environmental authority must, as soon as practicable, notify the **administering authority** of all relevant facts, matters and circumstances known concerning the disposal.

Schedule D: Monitoring and Reporting	
Condition number	**Condition**
10-D01	**Complaint Recording** All complaints received by the holder of this environmental authority relating to releases of contaminants from operations at the licensed place must be recorded and kept with the following details: (a) time, date and nature of complaint; (b) type of communication (telephone, letter, personal etc.); (c) name, contact address and contact telephone number of complainant (Note: if the complainant does not wish to be identified then "Not identified" is to be recorded); (d) response and investigation undertaken as a result of the complaint; (e) name of person responsible for investigating complaint; and (f) action taken as a result of the complaint investigation and signature of responsible person.
10-D02	**Report Submission** The holder of this environmental authority must ensure that the results of all monitoring performed in accordance with this environmental authority for the period covered by the return are submitted with the Annual Return.
10-D03	**Incident Recording** A record must be maintained of at least the following events: (a) the time, date and duration of equipment malfunctions where the failure of the equipment resulted in the release of contaminants reasonably likely to cause environmental harm; (b) any uncontrolled release of contaminants reasonably likely to cause environmental harm and (c) any emergency involving the release of contaminants reasonably likely to cause material or serious environmental harm requiring the use of fire fighting equipment.
10-D04	**Notification of Emergencies and Incidents** Where the holder of this environmental authority has not given notification to the **administering authority** under section 37 of the *Environmental Protection Act 1994*, as soon as practicable after becoming aware of any emergency or incident which results in the release of contaminants not in accordance, or reasonably expected to be not in accordance with the conditions of this environmental authority, the holder of this environmental authority must notify the **administering authority** of the release by telephone or facsimile.
10-D05	Where the holder of this environmental authority has not given notification to the **administering authority** under section 37 of the *Environmental Protection Act 1994*, the notification of emergencies or incidents as required by condition number (10-D4) must include but not be limited to the following: (i) the holder of the environmental authority; (ii) the location of the emergency or incident; (iii) the number of the environmental authority;

	(iv) the name and telephone number of the designated contact person; (v) the time of the release; (vi) the time the holder of the environmental authority became aware of the release; (vii) the suspected cause of the release; (viii) the environmental harm and or environmental nuisance caused, threatened, or to be caused by the release; and (ix) actions taken to prevent further any release and mitigate any environmental harm and or environmental nuisance caused by the release.
10-D06	Where the holder of this environmental authority has not given notification to the **administering authority** under section 37 of the *Environmental Protection Act 1994*, not more than 14 days following the initial notification of an emergency or incident, the holder of the environmental authority must provide written advice of the information supplied in accordance with condition number (10-D5) in addition to: (i) proposed actions to prevent a recurrence of the emergency or incident; (ii) outcomes of actions taken at the time to prevent or minimise environmental harm and or environmental nuisance.
10-D07	**Exception Reporting** The holder of this environmental authority must notify the **administering authority** in writing within 28 days of completion of analysis of any result of a monitoring program required by a condition of this environmental authority which indicates an exceedance of any limit specified in this environmental authority.
10-D08	The written notification required by condition number (10-D7) above must include: (a) the full analysis results, and (b) details of investigation or corrective actions taken, and (c) any subsequent analysis.
Schedule G: General Waste Disposal Facility	
Condition number	**Condition**
10-G01	**Design and Operating Criteria** The waste accepted at-the landfill facility must be in accordance with the Council's Waste Acceptance Criteria.
10-G02	The Waste Acceptance Criteria must be documented and submitted for approval to the **administering authority** by 1 August 1998.
10-G03	Area/s must be set aside for segregation and storage of recyclable solid wastes.
10-G04	The occurrence of exposed wastes must be confined to the working face of the landfill units and be minimised.
10-G05	No waste must be deposited beyond the boundaries of the landfill units.
10-G06	All wastes must be deposited in lifts not exceeding a vertical height of 3 meters.
10-G07	The working face of the landfill must not exceed 30 meters in width.
10-G08	Waste deposited within the landfill facility must be evenly and properly consolidated by mechanical plant at the end of each week.

10-G09	Putrescible wastes or domestic wastes must be deposited at least 2.0 metres above the highest regional water table or as otherwise approved based on the liner design and groundwater monitoring network.
10-G10	Deposited waste must be covered with 0.20 metre thick earthen material or other dense and incombustible alternative material of a thickness and nature acceptable to the **administering authority**, at the end of each week or at more frequent intervals if necessary, so that no putrescible wastes are exposed.
10-G11	Adequate cover material for at least two weeks operation must be stored and be readily available on the licensed site.
10-G12	The licensed premises must be appropriately fenced to restrict unauthorised access to the site, provide litter control and stock/animal control.
10-G13	The fence around the site must be maintained in good repair. A regular program of litter collection must be conducted to ensure that the site, fence and the surrounds of the site are kept in a tidy condition.
10-G14	The holder of this environmental authority must prominently display on the licensed site appropriate signs with the following information: • types of waste which must be deposited at the site and a contact telephone number for information on alternative disposal options; • prominent list of materials acceptable for recycling and the location/s for deposition of these on the site; • contact telephone number for information and complaints; • a warning sign indicating that unlawful disposal and unauthorised scavenging is prohibited; • a warning sign indicating that open burning is prohibited.
10-G15	**Fire prevention** The holder of this environmental authority must ensure that the fire fighting equipment is readily accessible at all times.
10-G16	A fire break must be provided and maintained in consultation with the Regional Fire Commander.
10-G17	**Public Health Issues** The holder of this environmental authority must take all practical measures to ensure that the environmentally relevant activity is conducted at all times in a nuisance free manner, particularly regarding fly breeding, mosquito breeding and rat harbourage and breeding.
10-G18	A program for the monitoring and control of rodents and insect pests must be established and maintained to the satisfaction of the **administering authority**.
10-G19	**Nuisance** No release of contaminants, including but not limited to odour, dust, smoke, fume, particulates and aerosols, is to cause or be likely to cause an environmental nuisance beyond the boundaries of the licensed place.
10-G20	**Water Pollution Control** Contaminants must not be directly or indirectly released from the licensed place to any waters, including groundwater, or bed and banks of any waters.

10-G21	Leachate must not be permitted to discharge beyond the boundaries of the licensed place.
10-G22	Diversion drainage structures must be in place to divert stormwater flows away from disposal areas.
10-G23	Stormwater runoff polluted by waste or leachate must not be permitted to discharge beyond the boundaries of the licensed place.
10-G24	By the date of the first annual return the holder of this environmental authority must submit to the **administering authority** a management plan to address the necessity for leachate management.
10-G25	**Site Rehabilitation** At cessation of waste disposal operations in a stage of the licensed place, a final cover consisting of at least 500 millimetres depth of compacted clean earth must be placed over the completed area.
10-G26	The final surface of any completed area of the licensed place must, after covering as specified in conditions above, be graded, drained and vegetated in such a manner as to minimise erosion and to prevent ponding of stormwater.
10-G27	Erosion and sediment control structures must be maintained at all times during the period of rehabilitation and checked, repaired or replaced as required after each min event.
10-G28	**Closure and Post-closure Care** The holder of this environmental authority must conduct post closure care of any landfill unit for 30 years or until it can be demonstrated to the **administering authority** that the site is geotechnically stable and will not release contaminants to the environment. Such care would comprise: (i) maintaining the integrity and effectiveness of any final cover; (ii) maintaining and operating the leachate collection system; (iii) monitoring the groundwater water quality; (iv) maintaining and operating the landfill gas monitoring system.
10-G29	The holder of this environmental authority must: (i) develop and implement a landfill unit rehabilitation plan in accordance with (ii) the requirements referred to in condition (10-G28); (iii) lodge with the **administering authority** the landfill unit rehabilitation plan proposal at least 12 months before the anticipated final receipt of wastes in the landfill unit for its review and comment; (iv) have due regard to this comment in the finalisation of the landfill unit rehabilitation plan.
10-G30	The holder of this environmental authority must begin closure activities of any landfill unit no later than 28 days after the date on which landfill unit receives the final recorded receipt of wastes.
10-G31	**Groundwater Monitoring** A groundwater monitoring system must be installed for every landfill unit. The system must include a sufficient number of wells installed at locations and depths which yield representative groundwater samples from the uppermost aquifer that establish:

	(i) background groundwater quality in hydraulically up-gradient or background well(s) that have not been affected by any potential leakage of contaminants to groundwater; (ii) quality of groundwater down-gradient of any potential leakage of contaminants to groundwater.
10-G32	Locations referred to in condition (10-G31) for groundwater monitoring facilities must be given with reference to horizontal co-ordinates of such facilities accurate to 1.0 meter.
10-G33	The point(s) of compliance referred to in condition (10-G31) for the groundwater monitoring system(s) must be situated not more than 150 meters from any landfill unit or the boundary of the landfill facility whichever is closest.
10-G34	By the first annual return the holder of this environmental authority must develop and implement a Groundwater Monitoring Program.
Schedule I: Definitions	
Condition number	**Condition**
3-I04	**Administering Authority** means Department of Environment and Science or its successor.

END OF ENVIRONMENTAL AUTHORITY